

# C404400DS

## Switch disconnecter, ComPacT NSX400NA DC, 4 poles, fixed, thermal current I<sub>th</sub> 400A



### Main

Range	ComPacT new generation
Product name	ComPacT NSX DC new generation
Device short name	NSX400NA DC
Product or component type	Switch disconnecter
Device application	Distribution
Poles description	4P
[I <sub>th</sub> ] conventional free air thermal current	400 A at 40 °C
[I <sub>e</sub> ] rated operational current	DC-22A: 400 A DC 750 V
[U <sub>e</sub> ] rated operational voltage	750 V DC
Network type	DC
Suitability for isolation	Yes conforming to EN/IEC 60947-3
Utilisation category	DC-22A
Breaking capacity code	NA
Contact position indicator	Yes
Visible break	No
Mounting mode	Fixed
[I <sub>cw</sub> ] rated short-time withstand current	7.5 kA during 1 s
[I <sub>cm</sub> ] rated short-circuit making capacity	7.5 kA switch-disconnector alone
Control type	Toggle
[U <sub>i</sub> ] rated insulation voltage	750 V DC
[U <sub>imp</sub> ] rated impulse withstand voltage	8 kV

### Complementary

Mounting support	Backplate
Upside connection	Front
Downside connection	Front
Connection pitch	45 mm
Mechanical durability	5000 cycles
Electrical durability	1000 cycles 750 V DC In
Width (W)	185 mm
Height (H)	255 mm
Depth (D)	110 mm
Net weight	7.8 kg
Standards	EN/IEC 60947-1 EN/IEC 60947-3
Product certifications	CE[RETURN]EAC[RETURN]CCC

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 62262
Electrical shock protection class	Class II
Pollution degree	3 conforming to IEC 60664-1
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.7 cm
Package 1 Width	20.0 cm
Package 1 Length	29.1 cm
Package 1 Weight	7.286 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
Halogen content performance	Halogen free plastic parts product