



Main

| | |
|--|---|
| Range | ComPacT new generation |
| Product name | ComPacT NSX new generation |
| Device short name | NSX400R |
| Product or component type | Circuit breaker |
| Device application | Distribution |
| Poles description | 3P |
| Protected poles description | 3D |
| [In] rated current | 320 A at 65 °C |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz |
| Network type | AC |
| Network frequency | 50/60 Hz |
| Suitability for isolation | Yes conforming to EN/IEC 60947-2 |
| Utilisation category | Category A |
| [Icu] rated ultimate short-circuit breaking capacity | 200 KA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 200 KA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 200 KA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 80 KA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2 65 KA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2 45 kA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Performance level | R 200 kA 415 V AC |
| Trip unit name | MicroLogic 6.3 E-M |
| Trip unit technology | Electronic |
| Trip unit protection functions | LSIG |
| Control type | Toggle |
| Circuit breaker mounting mode | Fixed |

Complementary

| | |
|---|---|
| [Ui] rated insulation voltage | 800 V AC 50/60 Hz |
| [Uiimp] rated impulse withstand voltage | 8 kV |
| [Ics] rated service short-circuit breaking capacity | 200 KA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 200 KA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 200 KA at 440 V AC 50/60 Hz conforming to IEC 60947-2 80 KA at 500 V AC 50/60 Hz conforming to IEC 60947-2 65 KA at 525 V AC 50/60 Hz conforming to IEC 60947-2 45 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Mechanical durability | 15000 cycles |
| Electrical durability | 12000 Cycles at 440 V In/2 6000 Cycles at 440 V In 6000 Cycles at 690 V In/2 3000 cycles at 690 V In |
| Power dissipation per pole | 12.29 W |

| | |
|--|---|
| Mounting support | Backplate |
| Mounting position | Horizontal and vertical Flat on the back |
| Upside connection | Front |
| Downside connection | Front |
| Connection pitch | 45 mm |
| Protection type | L : for overload protection (long time) So : for short time short-circuit protection I : for instantaneous short-circuit protection G : for ground fault protection |
| Trip unit rating | 320 A at 65 °C |
| Motor tripping class | 10 20 30 5 |
| Complementary motor protection | Stalled rotor Phase unbalance Protracted starting time Underload |
| Long-time pick-up adjustment type Ir (thermal protection) | Adjustable 9 settings |
| [Ir] long-time protection pick-up adjustment range | 160...320 A |
| Long-time protection delay adjustment type tr | Adjustable |
| [tr] long-time protection delay adjustment range | 120 S at 1.5 x Ir for trip class 5 6.5 S at 6 x Ir for trip class 5 5 S at 7.2 x Ir for trip class 5 240 S at 1.5 x Ir for trip class 10 13.5 S at 6 x Ir for trip class 10 10 S at 7.2 x Ir for trip class 10 480 S at 1.5 x Ir for trip class 20 26 S at 6 x Ir for trip class 20 20 S at 7.2 x Ir for trip class 20 720 S at 1.5 x Ir for trip class 30 38 S at 6 x Ir for trip class 30 30 s at 7.2 x Ir for trip class 30 |
| Thermal memory | 20 minutes before and after tripping |
| Short-time protection pick-up adjustment type Isd | Adjustable |
| [Isd] Short-time protection pick-up adjustment range | 5...13 x Ir |
| Short-time protection delay adjustment type tsd | Fixed |
| Instantaneous protection pick-up adjustment type li | Fixed |
| [li] instantaneous protection pick-up adjustment range | 4800 A |
| Ground-fault protection pick-up adjustment type Ig | Adjustable 9 settings |
| [Ig] ground-fault protection pick-up adjustment range | 0.6...1 x In for $In = 25$ A 0.3...1 x In for $In = 50$ A 0.2...1 x In for $In > 50$ A Ig enable on/off |
| Ground-fault protection time delay adjustment type tg | Adjustable 5 settings |
| [tg] ground-fault protection time delay adjustment range | 0...0.4 s |
| Earth-leakage protection | Without |
| Zone selective interlocking ZSI | With |
| Number of slots for electrical auxiliaries | 6 slot(s) |
| Local signalling | Flashing LED (green) for ready to operate LED 95 % Ith (red) for temperature over set point |
| Display type | LCD display |
| Type of measurement | Energy meter |
| Communication of data | Energy metering Protection and alarm settings Thermal image function Time-stamped histories and event tables Power quality Demand current and power Maintenance indicators Phase sequence Maximeters/Minimeters Instantaneous and demand values |

| | |
|------------|---------|
| Width (W) | 140 mm |
| Height (H) | 255 mm |
| Depth (D) | 110 mm |
| Net weight | 6.05 kg |

Environment

| | |
|---------------------------------------|--|
| Standards | EN/IEC 60947 |
| Product certifications | Marine[RETURN]EAC[RETURN]CCC |
| Overvoltage category | Class II |
| Electrical shock protection class | Class II |
| Pollution degree | 3 conforming to IEC 60664-1 |
| IP degree of protection | IP40 conforming to IEC 60529 |
| IK degree of protection | IK07 conforming to IEC 62262 |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...85 °C |
| Relative humidity | 0...95 % |
| Operating altitude | 0...2000 m without derating 2000 m...5000 m with derating |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 15.2 cm |
| Package 1 Width | 15.2 cm |
| Package 1 Length | 29.2 cm |
| Package 1 Weight | 5.82 kg |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | <input checked="" type="checkbox"/> REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| Mercury free | Yes |
| China RoHS Regulation | <input checked="" type="checkbox"/> China RoHS Declaration |
| RoHS exemption information | <input checked="" type="checkbox"/> Yes |
| Environmental Disclosure | <input checked="" type="checkbox"/> Product Environmental Profile |
| Circularity Profile | <input checked="" type="checkbox"/> End Of Life Information |
| PVC free | Yes |
| Halogen content performance | Halogen free plastic parts product |