



### Main

Range of product	Acti9
Product name	Acti9 ITA
Device short name	ITA
Product or component type	Yearly programmable time switch
Device application	Building
Battery type	Lithium
Number of channels	1
User language	Romanian English Danish German Spanish Italian Swedish French Norwegian Dutch Czech Hungarian Polish Finnish Portuguese
Colour tint	White (RAL 9003)

### Complementary

Maximum switching current	16 A - 250 V AC pf = 1 6 A - 250 V AC pf = 0.6
[Ue] rated operational voltage	230 V AC at 50/60 Hz
Accuracy	+/- 0.5 s/day 20 °C
Cycle duration	24 hours + 7 days + year
Maximum number of switchings	300
Minimum interval duration	1 s
Function available	Manual or software programming Cycle programming Time synchronisation via antenna possible External input for override Automatic winter/summer time changeover Pulse programming
Display type	Backlit LCD
Battery life	10 year(s)
Backup time	10 years time and program saving
Type of setting	Absence for holidays function PIN code
Connections - terminals	Screw terminals
Mounting support	DIN rail
9 mm pitches	4
Width	35.8 mm
Height	90 mm
Depth	63 mm
Function	Pulse programming
Absence for holidays	Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Time changeover	Automatic
Updated by	DCF77 GPS
Compatibility code	ITA
Market segment	Small commercial

## Environment

Ambient air temperature for operation	-30...55 °C
IP degree of protection	IP20

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.5 cm
Package 1 Width	7.8 cm
Package 1 Length	12.5 cm
Package 1 Weight	232.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	18
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	4.503 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins