



Main

Range compatibility	Lexium 62 ILM Lexium 32 Lexium 62 Lexium SD3 Lexium 52 Lexium 28 Lexium 32i
Gear box type	Straight teeth
Product or component type	Planetary gearbox
Device short name	GBX
Product compatibility	BMI (100 mm, 2 motor stacks) BMI (100 mm, 3 motor stacks) BMH (140 mm, 1 motor stacks) BMH (140 mm, 2 motor stacks) BSH (100 mm, 4 motor stacks) BSH (140 mm, 1 motor stacks) BSH (140 mm, 2 motor stacks) BRS3 BCH2 (100 mm, 1 motor stacks) BCH2 (100 mm, 2 motor stacks) BCH2 (130 mm, 1 motor stacks) BCH2 (130 mm, 2 motor stacks) BCH2 (130 mm, 3 motor stacks) BCH2 (130 mm, 4 motor stacks) SH3 MH3 ILM
Gearbox external diameter	120 mm
Reduction ratio	5:1

Complementary

Maximum torsional backlash	7 arc.min
Torsional rigidity	12 N.m/arcmin
Housing colour	Black
Housing material	Black anodized aluminium
Shaft material	C 45
Additional information	Lubricated for life
Service life in hours	30000 h at 100 rpm at 30 °C
Mounting position	Any position
Efficiency	96 %
Maximum radial force Fr	1500 N at 100 rpm, force applied at mid-distance from output shaft during 30000 hour at 30 °C
Maximum axial force Fa	2100 N at 100 rpm, during 30000 hour at 30°C
Moment of inertia	1.53 kg.cm ²
Continuous output torque	195 N.m at 100 rpm at 30 °C
Maximum output torque	312 N.m at 100 rpm at 30 °C
Net weight	6 kg
Input diameter	24.0 mm

Environment

Noise level	65 dB at 1 m, no-load
IP degree of protection	Shaft output: IP54
Ambient temperature for operation	-25...90 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.500 cm
Package 1 Width	12.500 cm
Package 1 Length	18.000 cm
Package 1 Weight	5.397 kg
Unit Type of Package 2	P06
Number of Units in Package 2	5
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	40.135 kg


Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Dimensions with Servo Motor Adaptation Kit



(1) GBK adaptation kit

(2) GBK adaptation kit related dimensions a1, c, Ø6, Ø7, Ø8 depend on the gearbox and servo motor combination

Ø8 shaft end adaptor in case motor shaft diameter is smaller than gearbox input coupling diameter

Values in mm

a2	a3	a4	a5	h	g	Ø1	Ø2	Ø3	Ø4	Ø5
99.5	55	50	5	28	8	115	80 h7	25 h7	M10 x 16	100

Values in in.

a2	a3	a4	a5	h	g	Ø1	Ø2	Ø3	Ø4	Ø5
3.92	2.17	1.97	0.19	1.10	0.31	4.53	3.15 h7	0.98 h7	M10 x 0.63	3.94