



Main

Range	TeSys
Device short name	GV4A
Product or component type	Auxiliary contact block
Device application	Signalling
Range compatibility	TeSys TeSys GV4 multifunction circuit breaker
Mounting location	Right side
Mounting mode	Clipped
Pole contact composition	2 NO + 2 NC

Complementary

[Ui] rated insulation voltage	250 V conforming to IEC 60947-1
[Ue] rated operational voltage	24...250 V AC 24...250 V DC
[Ith] conventional free air thermal current	5 A
Associated fuse rating	5 A gG conforming to IEC 60947-5-1
Mechanical durability	100000 cycles
Minimum switching current	2 mA
Minimum switching voltage	17 V
Rated operational power in VA	400 VA at 230...240 V AC-12
Rated operational power in W	50 W at 24 V DC-12

Environment

Environmental characteristic	Normal environment
------------------------------	--------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3 cm
Package 1 Width	9 cm
Package 1 Length	15.6 cm
Package 1 Weight	150 g
Unit Type of Package 2	S02
Number of Units in Package 2	18
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	3 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins