# ILM1402P11A0000

integrated servo motor - 12.5 Nm - 2000 rpm - keyed shaft - without brake





### Main

Range of product	PacDrive 3
Product or component type	Servo motor integrated drive
Device short name	ILM

Complementary

[Us] rated supply voltage	250700 V	
Continuous stall current	4.8 A	
Continuous stall torque	12.5 N.m	
Peak stall torque	55 N.m	
Nominal output power	1910 W	
Nominal torque	9.1 N.m	
Nominal speed	2000 rpm	
Maximum current Irms	24 A	
[In] rated current	3.7 A	
Shaft end	Keyed	
Second shaft	Without second shaft end	
Shaft diameter	24 mm	
Shaft length	50 mm	
Key width	40 mm	
Feedback type	Absolute single turn SinCos Hiperface	
Speed feedback resolution	128 periods	
Holding brake	Without	
Mounting support	International standard flange	
Motor flange size	140 mm	
Torque constant	2.6 N.m/A at 120 °C	
Back emf constant	173 V/krpm at 20 °C	
Number of motor poles	10	
Rotor inertia	12.68 kg.cm <sup>2</sup>	
Stator resistance	1.9 Ohm at 20 °C for Ph/Ph	
	1.32 Ohm at 120 °C for Ph/N	
Stator inductance	22 MH at 20 °C for Ph/Ph 11 mH at 120 °C for Ph/N	
Maximum radial force Fr	2430 N at 1000 rpm 1930 N at 2000 rpm	
Maximum axial force Fa	0.2 x Fr	
Type of cooling	Natural convection	
Length	309 mm	
Number of motor stacks	2	
Centring collar diameter	130 mm	
-		

Centring collar depth	3.5 mm
Number of mounting holes	4
Mounting holes diameter	11 mm
Circle diameter of the mounting holes	165 mm
Net weight	17.2 kg

# Environment

IP degree of protection	IP54	
g		

# **Packing Units**

•		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	26.0 cm	
Package 1 Width	20.0 cm	
Package 1 Length	59.0 cm	
Package 1 Weight	23.13 kg	

### Offer Sustainability

Onor Odolamability		
Sustainable offer status	Green Premium product  REACh Declaration	
REACh Regulation		
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
Mercury free	Yes	
China RoHS Regulation	☑ China RoHS Declaration	
RoHS exemption information	₽¥Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	☐ End Of Life Information	
PVC free	Yes	