

# KADCCAL

## K Series Replacement Calculator, For KDC and legacy MC Cooling



### Main

IP degree of protection	IP65
Location	Plant room
Range	KD Series
Product brand	Schneider Electric
Product or component type	Replacement equipment
Ambient air temperature for operation	5...55 °C
Ambient air temperature for storage	-25...60 °C
Range of product	K Series
Colour	Off white
Relative humidity	0...100 % RH, non-condensing
Storage Relative Humidity	0...100 % RH, non-condensing
[Us] rated supply voltage	161...264 V AC 12...36 V AC

### Complementary

Clamping connection capacity	$\leq 1 \text{ mm}^2$
Maximum power consumption in W	1 W
Material	Thermoplastic, PC 10 % GF with TPE: enclosure
Depth	47 mm
Height	102 mm
Width	166 mm

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.0 cm
Package 1 Width	19.5 cm
Package 1 Length	22.5 cm
Package 1 Weight	600.0 g

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.