

Product data sheet

Characteristics

KBB40ABG44W

End feed unit, Canalis KBB, 25/40A, right or left mounting, 2 circuits, compatible DALI, white RAL9003



Main

Range of product	Canalis
Device short name	KBB
Product compatibility	Canalis KBB busbar trunking 25...40 A
Offer type	Classic Control system
Product or component type	Feed unit
Conductors material	Aluminium
[Ie] rated operational current	40 A 25 A
[Ue] rated operational voltage	230...400 V
Number of circuits	2
Busbar trunking polarity	3L + N + PE L + N + PE
Protection type	Without protection
Control type	Communicating
Communication port protocol	DALI
Colour	White (RAL 9003)

Complementary

Provided equipment	End cover
Mounting location	Left
Mounting mode	By clips
Mounting support	Busbar
Connections - terminals	Terminal block - Pg 21 - screw clamp connector for 6...10 mm ²
Width	244 mm
Depth	103.5 mm
Height	75.5 mm
Net weight	400 g
Standards	IEC 61439-6

Environment

IP degree of protection	IP55 conforming to IEC 60529
-------------------------	------------------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.0 cm
Package 1 Width	11.0 cm
Package 1 Length	27.0 cm
Package 1 Weight	700.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	12

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	8.556 kg
Unit Type of Package 3	P06
Number of Units in Package 3	96
Package 3 Height	75.0 cm
Package 3 Width	60.0 cm
Package 3 Length	80.0 cm
Package 3 Weight	75.7 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------