

# KBB40ZFU

Universal fixing bracket, Canalis KBB, 25/40A, suspended on threaded rod or lateral, galvanized version



## Main

Range of product	Canalis
Product or component type	Bracket
Product compatibility	KBB
Fixing device mounting	Suspended on threaded rod
Maximum load	60 kg
Quantity per set	Set of 10

## Complementary

Accessory / separate part category	Fixing accessory
Width	55 mm
Depth	22 mm
Height	70.5 mm
Net weight	50 g

## Environment

Standards	IEC 61439-6
-----------	-------------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.000 cm
Package 1 Width	5.500 cm
Package 1 Length	6.500 cm
Package 1 Weight	50.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	5.500 cm
Package 2 Width	7.000 cm
Package 2 Length	13.500 cm
Package 2 Weight	500.000 g
Unit Type of Package 3	CAR
Number of Units in Package 3	220
Package 3 Height	18.000 cm
Package 3 Width	24.500 cm
Package 3 Length	38.000 cm
Package 3 Weight	11.790 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

## Contractual warranty

Warranty	18 months
----------	-----------