

# KBC1Z

Cam switch operating head, Harmony K, Ã~  
22mm, plastic, 45x45mm, metallic legend, key  
operated 60Â°, 601 A



## Main

|                           |                                                   |
|---------------------------|---------------------------------------------------|
| Range of product          | Harmony Series K                                  |
| Product or component type | Cam switch operating head                         |
| Component name            | KBC                                               |
| Product compatibility     | Front mounting bodies 12 and 20 A by Ø 22 mm hole |
| Cam switch head type      | With front plate 45 x 45 mm                       |
| Type of operator          | Key 601A                                          |
| Rotary handle padlocking  | Without                                           |
| Presentation of legend    | With metallic legend                              |
| Switching angle           | 60 °                                              |

## Complementary

|                       |                |
|-----------------------|----------------|
| Mechanical durability | 1000000 cycles |
| CAD overall width     | 45 mm          |
| CAD overall height    | 45 mm          |
| CAD overall depth     | 69 mm          |
| Net weight            | 0.063 kg       |
| Compatibility code    | KBC            |

## Environment

|                                       |                                                              |
|---------------------------------------|--------------------------------------------------------------|
| Protective treatment                  | TC                                                           |
| Ambient air temperature for operation | -25...55 °C                                                  |
| Ambient air temperature for storage   | -40...70 °C                                                  |
| Shock resistance                      | 30 gn conforming to IEC 68-2-27                              |
| Vibration resistance                  | 5 gn conforming to IEC 68-2-6 (f = 10...150 Hz)              |
| IP degree of protection               | IP65 conforming to IEC 529<br>IP65 conforming to NF C 20-010 |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 7.8 cm  |
| Package 1 Width              | 6.5 cm  |
| Package 1 Length             | 6.5 cm  |
| Package 1 Weight             | 69 g    |
| Unit Type of Package 2       | S02     |
| Number of Units in Package 2 | 15      |
| Package 2 Height             | 15 cm   |
| Package 2 Width              | 30 cm   |
| Package 2 Length             | 40 cm   |
| Package 2 Weight             | 1.49 kg |

## Offer Sustainability

|                            |                                                                                                                                                                                    |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| REACH Regulation           | <a href="#"> REACH Declaration</a>                                                                |
| REACH free of SVHC         | Yes                                                                                                                                                                                |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#"> EU RoHS Declaration</a> |
| Toxic heavy metal free     | Yes                                                                                                                                                                                |
| Mercury free               | Yes                                                                                                                                                                                |
| China RoHS Regulation      | <a href="#"> China RoHS Declaration</a>                                                           |
| RoHS exemption information | <a href="#"> Yes</a>                                                                              |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|