


# KRA2000EL45

Long feed unit for dry type transformer, Canalis KRA, aluminium, 2000A, 3L+N/3L+PE/3L+PEN, made to measure, grey RAL7030



## Main

|                                       |                                                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Range                                 | Canalis                                                                                                                                         |
| Product name                          | KR                                                                                                                                              |
| Product or component type             | Long feeder trunking                                                                                                                            |
| Device short name                     | KRA                                                                                                                                             |
| Product specific application          | Healthcare<br>Real estate and office buildings<br>Oil and gas<br>Mining minerals and metals<br>Water and waste water<br>Enterprise data centres |
| Device application                    | Feeder length                                                                                                                                   |
| Supply                                | Dry-type transformer                                                                                                                            |
| Material                              | Aluminium                                                                                                                                       |
| [Ie] rated operational current        | 2000 A at 35 °C                                                                                                                                 |
| Busbar/connection pads direction type | Edgewise to straight                                                                                                                            |
| Earth conductor                       | Standard earth                                                                                                                                  |
| Short-circuit level                   | Standard version                                                                                                                                |

## Complementary

|                                          |                                                                                                                                                                                                                                                                               |
|------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Housing material                         | Mineral epoxy resin                                                                                                                                                                                                                                                           |
| Contacts material                        | Tinned aluminium                                                                                                                                                                                                                                                              |
| [Ue] rated operational voltage           | 1000 V                                                                                                                                                                                                                                                                        |
| Network frequency                        | 50/60 Hz                                                                                                                                                                                                                                                                      |
| [Ui] rated insulation voltage            | 1000 V                                                                                                                                                                                                                                                                        |
| [Icw] rated short-time withstand current | 65 kA                                                                                                                                                                                                                                                                         |
| [Ipk] rated peak withstand current       | 143 kA                                                                                                                                                                                                                                                                        |
| Radiated magnetic field                  | 22.1 mT                                                                                                                                                                                                                                                                       |
| Thermal stress limit                     | 4225000 kA <sup>2</sup> .s                                                                                                                                                                                                                                                    |
| Maximum voltage drop                     | <0.005 V with power factor = 1 at 50 Hz with 1A for 100 m long<br><0.0069 V with power factor = 0.9 at 50 Hz with 1A for 100 m long<br><0.0072 V with power factor = 0.8 at 50 Hz with 1A for 100 m long<br><0.0074 V with power factor = 0.7 at 50 Hz with 1A for 100 m long |
| Mounting location                        | Outdoor<br>Indoor                                                                                                                                                                                                                                                             |
| Busbar incoming                          | Horizontal side                                                                                                                                                                                                                                                               |
| Polarity                                 | 3L + N or 3L + PE or 3L + PEN                                                                                                                                                                                                                                                 |
| Product certifications                   | EAC[RETURN]ATEX[RETURN]CE                                                                                                                                                                                                                                                     |
| Standards                                | IEC 61439-6                                                                                                                                                                                                                                                                   |
| Dimension type                           | Made to measure                                                                                                                                                                                                                                                               |
| Colour                                   | Grey (RAL 7030)                                                                                                                                                                                                                                                               |
| Linear load                              | 58 kg/m                                                                                                                                                                                                                                                                       |

## Environment

|                              |                                                                                                                                                                                                                                                   |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IP degree of protection      | IP68 conforming to IEC 60529                                                                                                                                                                                                                      |
| IK degree of protection      | IK10 conforming to IEC 62262                                                                                                                                                                                                                      |
| Pollution degree             | 3                                                                                                                                                                                                                                                 |
| Fire resistance              | 760 °C 180 min conforming to IEC 60331-1                                                                                                                                                                                                          |
| Derating factor              | 0...35 °C (100 % of In)<br>35...40 °C (96 % of In)<br>40...45 °C (89 % of In)<br>45...50 °C (84 % of In)<br>50...55 °C (78 % of In)                                                                                                               |
| Operating altitude           | 1000 m 100 % of In (indoor)<br>2000 m 99 % of In (indoor)<br>3000 m 96 % of In (indoor)<br>4000 m 90 % of In (indoor)<br>1000 m 98 % of In (outdoor)<br>2000 m 94 % of In (outdoor)<br>3000 m 89 % of In (outdoor)<br>4000 m 83 % of In (outdoor) |
| Environmental characteristic | EMC directive conforming to IEC 61439-6                                                                                                                                                                                                           |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 28.0 cm   |
| Package 1 Width              | 43.0 cm   |
| Package 1 Length             | 270.0 cm  |
| Package 1 Weight             | 164.43 kg |

## Offer Sustainability

|                             |                                                                                                                             |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status    | Green Premium product                                                                                                       |
| REACH Regulation            | <a href="#">REACH Declaration</a>                                                                                           |
| REACH free of SVHC          | Yes                                                                                                                         |
| EU RoHS Directive           | Compliant <a href="#">EU RoHS Declaration</a>                                                                               |
| Toxic heavy metal free      | Yes                                                                                                                         |
| Mercury free                | Yes                                                                                                                         |
| China RoHS Regulation       | <a href="#">China RoHS Declaration</a>                                                                                      |
| RoHS exemption information  | <a href="#">Yes</a>                                                                                                         |
| Environmental Disclosure    | <a href="#">Product Environmental Profile</a>                                                                               |
| Circularity Profile         | <a href="#">End Of Life Information</a>                                                                                     |
| WEEE                        | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Halogen content performance | Halogen free product                                                                                                        |