



#### Main

Range	Canalis
Product name	KR
Product or component type	Electrical and mechanical jointing
Device short name	KRA
Range compatibility	Canalis KR
Accessory / separate part category	Connection accessory
Device application	Jointing
Material	Aluminium
[Ie] rated operational current	4000 A with aluminium
Polarity	3L + N + PE

#### Complementary

Housing material	Mineral epoxy resin
Contacts material	Tinned aluminium
[Ue] rated operational voltage	1000 V
Earth conductor	Standard earth
Mounting location	Indoor Outdoor
Mounting support	Self-tapping screw
Product certifications	ATEX[RETURN]CE[RETURN]EAC
Standards	IEC 61439-6
Fixing mode	By 4 bolts
Tightening torque	84 N.m
Width	120 mm
Height	460 mm
Colour	Grey (RAL 7030)
Quantity per set	Set of 1

#### Environment

IP degree of protection	IP68 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262
Pollution degree	3

#### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	46.0 cm
Package 1 Width	12.0 cm
Package 1 Length	30.0 cm
Package 1 Weight	43.155 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 Yes
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	 <a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product