# Product data sheet
Characteristics

KRB0130ZA49

Vertical wall guiding support, Canalis KR, vertical busbar trunking, 1250A KRA, 1600A KRC, 3/4 conductors busbar

Green Premium™

Main

Range	Canalis
Product name	KR
Product or component type	Guiding support
Device short name	KRB

Complementary

Accessory / separate part category	Support accessory
Fixing device mounting	Wall mounting
Mounting position	Vertical
[Ie] rated operational current	1250 A with aluminium 1600 A with copper
Busbar trunking polarity	3L + N or 3L + PE or 3L + PEN 3L
Material	Stainless steel 316
Standards	IEC 61439-2 IEC 61439-6
Width	100 mm
Height	130 mm
Quantity per set	Set of 1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.0 cm
Package 1 Width	26.5 cm
Package 1 Length	28.4 cm
Package 1 Weight	3.21 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

Life Is On | Schneider Electric