
# KRB0230FM10

Fire rated casting mould, Canalis KR, 2000A for KRA, 2500A for KRC, for junction blocks, 3/4 conductors





## Main

Range	Canalis
Product name	KR
Product or component type	Casting mould
Device short name	KRB
Range compatibility	Canalis KR KRA[RETURN]Canalis KR KRC
Accessory / separate part category	Coupling accessory
[le] rated operational current	1600 A with aluminium 2000 A with copper
Busbar trunking polarity	3L + N or 3L + PE or 3L + PEN 3L
Length	360 mm

#### Complementary

Width	180 mm	_
Height	310 mm	_
Quantity per set	Set of 1	_
Kit composition	8 x neoprene seal 2 x mould 2 x C-profile	_

### **Packing Units**

PCE	
1	
23.0 cm	
10.0 cm	
30.0 cm	
14.49 kg	
	1 23.0 cm 10.0 cm 30.0 cm

## Offer Sustainability

Green Premium product
☑ REACh Declaration
Yes
Compliant EEU RoHS Declaration
Yes
Yes
China RoHS Declaration
₽¥Yes
Product Environmental Profile
<sup>™</sup> End Of Life Information
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen free product

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.