Product data sheet
Characteristics

# KRB0270FM10

Fire rated casting mould, Canalis KR, 2500A for KRA, 3200A for KRC, for junction blocks, 3/4 conductors

Green Premium™

Main

Range	Canalis
Product name	KR
Product or component type	Casting mould
Device short name	KRB
Range compatibility	Canalis KR KRA Canalis KR KRC
Accessory / separate part category	Coupling accessory
[Ie] rated operational current	2000 A with aluminium 2500 A with copper
Busbar trunking polarity	3L + N or 3L + PE or 3L + PEN 3L
Length	360 mm

Complementary

Width	180 mm
Height	350 mm
Quantity per set	Set of 1
Kit composition	8 x neoprene seal 2 x mould 2 x C-profile

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	27.0 cm
Package 1 Width	10.0 cm
Package 1 Length	30.0 cm
Package 1 Weight	17.01 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product