



Main

| | |
|------------------------------------|---|
| Range | Canalis |
| Product name | KR |
| Product or component type | Casting mould |
| Device short name | KRB |
| Range compatibility | Canalis KR KRA[RETURN]Canalis KR KRC |
| Accessory / separate part category | Coupling accessory |
| [Ie] rated operational current | 3200 A with aluminium 4000 A with copper |
| Busbar trunking polarity | 3L 3L + N or 3L + PE or 3L + PEN |
| Length | 320 mm |

Complementary

| | |
|------------------|---|
| Width | 140 mm |
| Height | 420 mm |
| Quantity per set | Set of 1 |
| Kit composition | 8 x neoprene seal 2 x mould 2 x C-profile |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 38.0 cm |
| Package 1 Width | 10.0 cm |
| Package 1 Length | 30.0 cm |
| Package 1 Weight | 23.94 kg |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Halogen content performance | Halogen free product |