

KSC800DLC401

Elbow, Canalis KSC800, copper, 800A, fixed dimensions (A/B 290mm), turns right or left, 3L +N+PE/3L+PE, white RAL9001



Main

Range of product	Canalis
Product name	KS
Device short name	KSC
Offer type	Classic
Product or component type	Elbow
Busbar description	Standard
Product compatibility	Canalis KSC busbar trunking 630...800 A
Device application	Change direction
Conductors material	Copper
Busbar trunking polarity	3L + N + PE
[Ie] rated operational current	800 A at 35 °C
IP degree of protection	IP55 conforming to IEC 60529
[Ue] rated operational voltage	230...690 V
Network frequency	50/60 Hz
Operating angle	90 °
Direction change type	Direction 1: edgewise to right - Direction 2: edgewise to left -
Colour	White (RAL 9001)
Dimension type	Fix

Complementary

Length	290 Mm for side A 290 mm for side B
Width	113 mm
Height	146 mm
Mounting location	On trunking
Mounting position	Any position
Electrical connection	Lubricated sliding contact
Mounting mode	By screws
Standards	IEC 61439-1 IEC 61439-6

Environment

IK degree of protection	IK08 conforming to IEC 62262
-------------------------	------------------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.0 cm
Package 1 Width	35.2 cm
Package 1 Length	48.8 cm
Package 1 Weight	20.0 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins