


KTA1250EB320

Straight length, Canalis KTA, aluminium, 1250A, 3L+PE, fixed length 2m, 1 outlet for bolt on tap off unit, RAL9001



Main

Range	Canalis
Product name	KT
Product or component type	Busbar trunking
Busbar description	Distribution length
Device short name	KTA
Tap-off unit compatibility	Bolt-on tap-off unit from Canalis - KT
Device application	High power distribution
Material	Aluminium
[Ie] rated operational current	1250 A at 35 °C
Polarity	3L + PE
Number of tap-off outlets	1
Nominal output current	400...1250 A
Earth conductor	Standard earth
Short-circuit level	Standard version
Length	2000 mm
Provided equipment	Joining unit Trunking unit

Complementary

Housing material	Polyester film
Contacts material	Copper
[Ue] rated operational voltage	1000 V
Network frequency	50/60 Hz
[Ui] rated insulation voltage	1000 V
[Icw] rated short-time withstand current	50 kA
[Ipk] rated peak withstand current	110 kA
Electrical connection	Bolted connection
Radiated magnetic field	0.75 µT
Thermal stress limit	2500000 kA ² .s
THDI	0...15 % 1250 A 15...33 % 1600 A 33...100 % 2000 A
Maximum voltage drop	<0.0049 V with power factor = 1 at 50 Hz with 1A for 100 m long <0.005 V with power factor = 0.9 at 50 Hz with 1A for 100 m long <0.0047 V with power factor = 0.8 at 50 Hz with 1A for 100 m long <0.0043 V with power factor = 0.7 at 50 Hz with 1A for 100 m long
Mounting mode	By hook
Mounting support	Pendant Cantilever arm
Installation direction	Horizontal Vertical
Neutral position	Right
Standards	IEC 61439-1 IEC 61439-6
Dimension type	Fix
Width	140 mm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Height	124 mm
Colour	White (RAL 9001)
Net weight	32 kg
Linear load	16 kg/m

Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262
Derating factor	0...35 °C (100 % of In) 35...40 °C (97 % of In) 40...45 °C (93 % of In) 45...50 °C (90 % of In) 50...55 °C (86 % of In)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.4 cm
Package 1 Width	14.0 cm
Package 1 Length	200.0 cm
Package 1 Weight	36.0 kg