


Product data sheet

Characteristics

KTA1600ET72C

Straight transport length, Canalis KTA, aluminium, 1600A, 3L+N+PER (Cu), high Icw, made to measure 2-2.5m, RAL9001



Main

Range	Canalis
Product name	KT
Product or component type	Busbar trunking
Busbar description	Transport length
Device short name	KTA
Device application	Feeder length
Material	Aluminium
[Ie] rated operational current	1600 A at 35 °C
Polarity	3L + N + PER
Number of tap-off outlets	0
Earth conductor	Reinforced
Short-circuit level	Reinforced version
Length	2001...2500 mm
Provided equipment	Trunking unit Jointing unit

Complementary

Housing material	Polyester film
Contacts material	Copper
[Ue] rated operational voltage	1000 V
Network frequency	50/60 Hz
[Ui] rated insulation voltage	1000 V
[Icw] rated short-time withstand current	85 kA
[Ipk] rated peak withstand current	187 kA
Radiated magnetic field	0.9 µT
Thermal stress limit	7225000 kA ² s
THDI	0...15 % 1600 A 15...33 % 2000 A 33...100 % 2500 A
Maximum voltage drop	<0.0037 V with power factor = 1 at 50 Hz with 1A for 100 m long <0.0038 V with power factor = 0.9 at 50 Hz with 1A for 100 m long <0.0036 V with power factor = 0.8 at 50 Hz with 1A for 100 m long <0.0034 V with power factor = 0.7 at 50 Hz with 1A for 100 m long
Mounting mode	By hook
Mounting support	Pendant Cantilever arm
Installation direction	Horizontal Vertical
Neutral position	Right
Standards	IEC 61439-6 IEC 61439-1
Dimension type	Made to measure
Width	146 mm
Height	194 mm
Colour	White (RAL 9001)
Linear load	26 kg/m

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262
Derating factor	0...35 °C (100 % of I_n) 35...40 °C (97 % of I_n) 40...45 °C (93 % of I_n) 45...50 °C (90 % of I_n) 50...55 °C (86 % of I_n)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	492.76 cm
Package 1 Width	14.6 cm
Package 1 Length	250.0 cm
Package 1 Weight	68.25 kg