


# KTA2500DB310

Straight expansion unit, Canalis KTA, aluminium, 2500A, 3L+PE, fixed length 1m, white RAL9001



## Main

|                                |                               |
|--------------------------------|-------------------------------|
| Range                          | Canalis                       |
| Product name                   | KT                            |
| Product or component type      | Expansion unit                |
| Busbar description             | Flexible bar                  |
| Device short name              | KTA                           |
| Device application             | Feeder length                 |
| Material                       | Aluminium                     |
| [Ie] rated operational current | 2500 A at 35 °C               |
| Polarity                       | 3L + PE                       |
| Number of tap-off outlets      | 0                             |
| Length                         | 1000 mm                       |
| Provided equipment             | Joining unit<br>Trunking unit |

## Complementary

|  |  |
|--|--|
| Housing material                         | Polyester film   |
| Contacts material                        | Copper   |
| [Ue] rated operational voltage           | 1000 V   |
| Network frequency                        | 50/60 Hz   |
| [Ui] rated insulation voltage            | 1000 V   |
| [Icw] rated short-time withstand current | 113 kA   |
| [Ipk] rated peak withstand current       | 248 kA   |
| Radiated magnetic field                  | 1.6 µT   |
| Thermal stress limit                     | 6400000 kA <sup>2</sup> .s   |
| THDI                                     | 0...15 % 2500 A<br>15...33 % 3200 A<br>33...100 % 4000 A   |
| Maximum voltage drop                     | <0.0024 V with power factor = 1 at 50 Hz with 1A for 100 m long<br><0.0025 V with power factor = 0.9 at 50 Hz with 1A for 100 m long<br><0.0024 V with power factor = 0.8 at 50 Hz with 1A for 100 m long<br><0.0022 V with power factor = 0.7 at 50 Hz with 1A for 100 m long |
| Mounting mode                            | By hook  |
| Mounting support                         | Cantilever arm<br>Pendant  |
| Installation direction                   | Horizontal<br>Vertical   |
| Horizontal distance                      | 30 m   |
| Neutral position                         | Right  |
| Standards                                | IEC 61439-1<br>IEC 61439-6   |
| Dimension type                           | Fix  |
| Width                                    | 140 mm   |
| Height                                   | 244 mm   |
| Colour                                   | White (RAL 9001)   |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|             |         |
|-------------|---------|
| Net weight  | 25 kg   |
| Linear load | 25 kg/m |

## Environment

|                         |   |
|-------------------------|---|
| IP degree of protection | IP55 conforming to IEC 60529  |
| IK degree of protection | IK08 conforming to IEC 62262  |
| Derating factor         | 0...35 °C (100 % of In)<br>35...40 °C (97 % of In)<br>40...45 °C (93 % of In)<br>45...50 °C (90 % of In)<br>50...55 °C (86 % of In) |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 14.0 cm  |
| Package 1 Width              | 28.0 cm  |
| Package 1 Length             | 100.0 cm |
| Package 1 Weight             | 26.0 kg  |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Compliant with Exemptions   |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |
| RoHS exemption information | <a href="#">Yes</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | <a href="#">End Of Life Information</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |