

KTA2500ED7203

Straight distribution length, Canalis KTA, aluminium, 2500A, 3L+N+PER(Cu), high Icw, fixed length 2m, 3 outlets, RAL9001



Main

Range	Canalis
Product name	KT
Product or component type	Busbar trunking
Busbar description	Distribution length
Device short name	KTA
Tap-off unit compatibility	Plug-in tap-off unit from Canalis KS Plug-in tap-off unit from Canalis KT
Device application	High power distribution
Material	Aluminium
[Ie] rated operational current	2500 A at 35 °C
Polarity	3L + N + PER
Number of tap-off outlets	3
Nominal output current	25...630 A
Earth conductor	Reinforced
Short-circuit level	Reinforced version
Length	2000 mm
Provided equipment	Joining unit Trunking unit

Complementary

Housing material	Polyester film
Contacts material	Copper
[Ue] rated operational voltage	1000 V
Network frequency	50/60 Hz
[Ui] rated insulation voltage	1000 V
[Icw] rated short-time withstand current	113 kA
[Ipk] rated peak withstand current	248 kA
Electrical connection	Sliding contact
Radiated magnetic field	1.6 µT
Thermal stress limit	12769000 kA².s
THDI	0...15 % 2500 A 15...33 % 3200 A 33...100 % 4000 A
Maximum voltage drop	<0.0024 V with power factor = 1 at 50 Hz with 1A for 100 m long <0.0025 V with power factor = 0.9 at 50 Hz with 1A for 100 m long <0.0024 V with power factor = 0.8 at 50 Hz with 1A for 100 m long <0.0022 V with power factor = 0.7 at 50 Hz with 1A for 100 m long
Mounting mode	By hook
Mounting support	Cantilever arm Pendant
Installation direction	Horizontal Vertical
Neutral position	Right
Tap-off unit interval	500 mm

Standards	IEC 61439-1 IEC 61439-6
Dimension type	Fix
Width	140 mm
Height	244 mm
Colour	White (RAL 9001)
Net weight	72 kg
Linear load	36 kg/m

Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262
Derating factor	0...35 °C (100 % of In) 35...40 °C (97 % of In) 40...45 °C (93 % of In) 45...50 °C (90 % of In) 50...55 °C (86 % of In)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.4 cm
Package 1 Width	14.0 cm
Package 1 Length	200.0 cm
Package 1 Weight	74.0 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins