


# KTA2500ER51

Straight feed unit, Canalis KTA, aluminium, 2500A, 3L+N+PER, fixed dimensions, neutral N1, white RAL9001



## Main

|                                |                                         |
|--------------------------------|-----------------------------------------|
| Range                          | Canalis                                 |
| Product name                   | KT                                      |
| Product or component type      | Straight feeder trunking                |
| Device short name              | KTA                                     |
| Device application             | Feeder length                           |
| Supply                         | Switchboard<br>Oil-immersed transformer |
| Material                       | Aluminium                               |
| [Ie] rated operational current | 2500 A at 35 °C                         |
| Neutral position               | Right                                   |
| Earth conductor                | Reinforced                              |
| Short-circuit level            | Standard version                        |
| Provided equipment             | Trunking unit                           |

## Complementary

|                                          |                                                                                                                                                                                                                                                                                |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Housing material                         | Polyester film                                                                                                                                                                                                                                                                 |
| Contacts material                        | Copper                                                                                                                                                                                                                                                                         |
| [Ue] rated operational voltage           | 1000 V                                                                                                                                                                                                                                                                         |
| Network frequency                        | 50/60 Hz                                                                                                                                                                                                                                                                       |
| [Ui] rated insulation voltage            | 1000 V                                                                                                                                                                                                                                                                         |
| [Icw] rated short-time withstand current | 80 kA                                                                                                                                                                                                                                                                          |
| [Ipk] rated peak withstand current       | 176 kA                                                                                                                                                                                                                                                                         |
| Radiated magnetic field                  | 1.6 µT                                                                                                                                                                                                                                                                         |
| Thermal stress limit                     | 6400000 kA².s                                                                                                                                                                                                                                                                  |
| THDI                                     | 0...15 % 2500 A<br>15...33 % 3200 A<br>33...100 % 4000 A                                                                                                                                                                                                                       |
| Maximum voltage drop                     | <0.0024 V with power factor = 1 at 50 Hz with 1A for 100 m long<br><0.0025 V with power factor = 0.9 at 50 Hz with 1A for 100 m long<br><0.0024 V with power factor = 0.8 at 50 Hz with 1A for 100 m long<br><0.0022 V with power factor = 0.7 at 50 Hz with 1A for 100 m long |
| Mounting mode                            | By screws                                                                                                                                                                                                                                                                      |
| Mounting support                         | Plate                                                                                                                                                                                                                                                                          |
| Polarity                                 | 3L + N + PER                                                                                                                                                                                                                                                                   |
| Number of tap-off outlets                | 0                                                                                                                                                                                                                                                                              |
| Standards                                | IEC 61439-1<br>IEC 61439-6                                                                                                                                                                                                                                                     |
| Dimension type                           | Fix                                                                                                                                                                                                                                                                            |
| Connection pitch                         | 115 mm                                                                                                                                                                                                                                                                         |
| Width                                    | 545 mm                                                                                                                                                                                                                                                                         |
| Depth                                    | 350 mm                                                                                                                                                                                                                                                                         |
| Height                                   | Direction 1: 235 mm                                                                                                                                                                                                                                                            |
| Colour                                   | White (RAL 9001)                                                                                                                                                                                                                                                               |
| Linear load                              | 30 kg/m                                                                                                                                                                                                                                                                        |

## Environment

|                         |                                                                                                                                     |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| IP degree of protection | IP55 conforming to IEC 60529                                                                                                        |
| IK degree of protection | IK08 conforming to IEC 62262                                                                                                        |
| Derating factor         | 0...35 °C (100 % of In)<br>35...40 °C (97 % of In)<br>40...45 °C (93 % of In)<br>45...50 °C (90 % of In)<br>50...55 °C (86 % of In) |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 35.0 cm |
| Package 1 Width              | 45.0 cm |
| Package 1 Length             | 55.0 cm |
| Package 1 Weight             | 21.2 kg |

## Offer Sustainability

|                            |                                                                                                                             |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                       |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                           |
| REACH free of SVHC         | Yes                                                                                                                         |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a>                                                                               |
| Toxic heavy metal free     | Yes                                                                                                                         |
| Mercury free               | Yes                                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                                                                                      |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                         |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                               |
| Circularity Profile        | <a href="#">End Of Life Information</a>                                                                                     |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |