


KTA4000EB740

Straight length, Canalis KTA, aluminium, 4000A, 3L+N+PER, high I_{cw}, fixed length 4m, 2 outlets for bolt on tap off unit



Main

Range	Canalis
Product name	KT
Product or component type	Busbar trunking
Busbar description	Distribution length
Device short name	KTA
Tap-off unit compatibility	Bolt-on tap-off unit from Canalis - KT
Device application	High power distribution
Material	Aluminium
[I _e] rated operational current	4000 A at 35 °C
Polarity	3L + N + PER
Number of tap-off outlets	2
Nominal output current	400...1250 A
Earth conductor	Reinforced
Short-circuit level	Reinforced version
Length	4000 mm
Provided equipment	Trunking unit Joining unit

Complementary

Housing material	Polyester film
Contacts material	Copper
[U _e] rated operational voltage	1000 V
Network frequency	50/60 Hz
[U _i] rated insulation voltage	1000 V
[I _{cw}] rated short-time withstand current	120 kA
[I _{pk}] rated peak withstand current	264 kA
Electrical connection	Bolted connection
Radiated magnetic field	3 μT
Thermal stress limit	14400000 kA ² .s
THDI	0...15 % 4000 A
Maximum voltage drop	<0.0015 V with power factor = 1 at 50 Hz with 1A for 100 m long <0.0016 V with power factor = 0.9 at 50 Hz with 1A for 100 m long <0.0015 V with power factor = 0.8 at 50 Hz with 1A for 100 m long <0.0015 V with power factor = 0.7 at 50 Hz with 1A for 100 m long
Mounting mode	By hook
Mounting support	Pendant Cantilever arm
Installation direction	Horizontal Vertical
Neutral position	Right
Tap-off unit interval	2000 mm
Standards	IEC 61439-6 IEC 61439-1
Dimension type	Fix
Width	140 mm
Height	404 mm

Colour	White (RAL 9001)
Net weight	224 kg
Linear load	56 kg/m

Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262
Derating factor	0...35 °C (100 % of In) 35...40 °C (97 % of In) 40...45 °C (93 % of In) 45...50 °C (90 % of In) 50...55 °C (86 % of In)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	40.4 cm
Package 1 Width	400.0 cm
Package 1 Length	14.0 cm
Package 1 Weight	209.3 kg