



Main

Range	Canalis
Product name	KT
Product or component type	Support
Product compatibility	Canalis KTA busbar trunking 800... 5000 A[RETURN]Canalis KTC busbar trunking 1000...6300 A
Accessory / separate part category	Support accessory
Fixing device mounting	Suspended on threaded rod
Busbar position	Edgewise Horizontal
Device composition	Support Threaded rod
Distance between supports	3 m

Complementary

Length	220 mm
Width	40 mm
Height	40 mm
Net weight	2.8 kg
Quantity per set	Set of 1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	50.0 cm
Package 1 Width	100.0 cm
Package 1 Length	10.0 cm
Package 1 Weight	6.0 kg

Offer Sustainability

Sustainable offer status	Green Premium product
RECh Regulation	RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

PVC free	Yes
Halogen content performance	Halogen free product
