



## Main

Range of product	Canalis
Range compatibility	Canalis KT busbar trunking
Product or component type	Tap-off unit
Busbar trunking compatibility	Canalis KT busbar trunking with KS type plug-in
[Ie] rated operational current	800...1000 A at 35 °C
Protection type	Circuit breaker: NS800...1000
Provided equipment	Circuit-breaker to be ordered separately
Mounting mode	Bolt-on
Tap-off unit polarity	3L+PEN

## Complementary

Device application	High power distribution
[Ue] rated operational voltage	500 V
[Uimp] rated impulse withstand voltage	8 kV
[Ui] rated insulation voltage	500 V
Network frequency	50/60 Hz
Control type	Rotary handle
Electrical connection	Bolted connection 300 mm <sup>2</sup> (x4) - for L/N Bolted connection 200 mm <sup>2</sup> (x1) - for PE
Door/cover opening side	Front
Standards	IEC 61439-1 IEC 61439-6
Colour	White (RAL 9001)
18 mm pitches	63
Width	1130 mm
Depth	330 mm
Height	550 mm
Net weight	45 kg

## Environment

IP degree of protection	IP54 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	45.0 cm
Package 1 Width	118.0 cm
Package 1 Length	55.0 cm
Package 1 Weight	50.0 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins