

# KTC3200ET73E

Straight transport length, Canalis KTC, copper, 3200A, 3L+N+PER (Cu), high I<sub>cw</sub>, made to measure length 3-3.5m, RAL9001



## Main

|                                             |                               |
|---------------------------------------------|-------------------------------|
| Range                                       | Canalis                       |
| Product name                                | KT                            |
| Product or component type                   | Busbar trunking               |
| Busbar description                          | Transport length              |
| Device short name                           | KTC                           |
| Device application                          | Feeder length                 |
| Material                                    | Copper                        |
| [I <sub>e</sub> ] rated operational current | 3200 A at 35 °C               |
| Polarity                                    | 3L + N + PER                  |
| Number of tap-off outlets                   | 0                             |
| Earth conductor                             | Reinforced                    |
| Short-circuit level                         | Reinforced version            |
| Length                                      | 3001...3499 mm                |
| Provided equipment                          | Joining unit<br>Trunking unit |

## Complementary

|                                                       |                                                                                                                                                                                                                                                                                |
|-------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Housing material                                      | Polyester film                                                                                                                                                                                                                                                                 |
| Contacts material                                     | Copper                                                                                                                                                                                                                                                                         |
| [U <sub>e</sub> ] rated operational voltage           | 1000 V                                                                                                                                                                                                                                                                         |
| Network frequency                                     | 50/60 Hz                                                                                                                                                                                                                                                                       |
| [U <sub>i</sub> ] rated insulation voltage            | 1000 V                                                                                                                                                                                                                                                                         |
| [I <sub>cw</sub> ] rated short-time withstand current | 113 kA                                                                                                                                                                                                                                                                         |
| [I <sub>pk</sub> ] rated peak withstand current       | 248 kA                                                                                                                                                                                                                                                                         |
| Radiated magnetic field                               | 1.6 µT                                                                                                                                                                                                                                                                         |
| Thermal stress limit                                  | 12769000 kA².s                                                                                                                                                                                                                                                                 |
| THDI                                                  | 33...100 % 2000 A<br>15...33 % 2500 A<br>0...15 % 3200 A                                                                                                                                                                                                                       |
| Maximum voltage drop                                  | <0.0015 V with power factor = 0.8 at 50 Hz with 1A for 100 m long<br><0.0013 V with power factor = 1 at 50 Hz with 1A for 100 m long<br><0.0015 V with power factor = 0.9 at 50 Hz with 1A for 100 m long<br><0.0014 V with power factor = 0.7 at 50 Hz with 1A for 100 m long |
| Mounting mode                                         | By hook                                                                                                                                                                                                                                                                        |
| Mounting support                                      | Pendant<br>Cantilever arm                                                                                                                                                                                                                                                      |
| Installation direction                                | Horizontal<br>Vertical                                                                                                                                                                                                                                                         |
| Neutral position                                      | Right                                                                                                                                                                                                                                                                          |
| Standards                                             | IEC 61439-6<br>IEC 61439-1                                                                                                                                                                                                                                                     |
| Dimension type                                        | Made to measure                                                                                                                                                                                                                                                                |
| Width                                                 | 146 mm                                                                                                                                                                                                                                                                         |
| Height                                                | 274 mm                                                                                                                                                                                                                                                                         |

|             |                  |
|-------------|------------------|
| Colour      | White (RAL 9001) |
| Linear load | 71 kg/m          |

## Environment

|                         |                                                                                                                                     |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| IP degree of protection | IP55 conforming to IEC 60529                                                                                                        |
| IK degree of protection | IK08 conforming to IEC 62262                                                                                                        |
| Derating factor         | 0...35 °C (100 % of In)<br>35...40 °C (95 % of In)<br>40...45 °C (90 % of In)<br>45...50 °C (84 % of In)<br>50...55 °C (79 % of In) |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 695.96 cm |
| Package 1 Width              | 14.6 cm   |
| Package 1 Length             | 350.0 cm  |
| Package 1 Weight             | 261.0 kg  |

## Offer Sustainability

|                            |                                                                                                                                   |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                             |
| REACH Regulation           |  <a href="#">REACH Declaration</a>               |
| EU RoHS Directive          | Compliant with Exemptions                                                                                                         |
| Mercury free               | Yes                                                                                                                               |
| China RoHS Regulation      |  <a href="#">China RoHS Declaration</a>        |
| RoHS exemption information |  <a href="#">Yes</a>                           |
| Environmental Disclosure   |  <a href="#">Product Environmental Profile</a> |
| Circularity Profile        |  <a href="#">End Of Life Information</a>       |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins       |