



Main

Range	TeSys
Device short name	LA9G
Product or component type	Switch module
Quantity per set	Set of 3

Complementary

Product compatibility	LC1G630...800
Accessory / separate part type	Kit
Maximum [I _e] rated operational current	1050 A AC-1 ≤ 440 V at 40 °C 800 A AC-3 ≤ 440 V at 40 °C
Poles description	3P
Connections - terminals	Bolted connection
Height	127.5 mm
Width	284 mm
Depth	202 mm
Net weight	8.5 kg

Environment

Pollution degree	3 conforming to IEC 60947-1
Operating altitude	3000 m without power derating 5000 m with derating factor
Standards	EN/IEC 60947-4-1 UL 60947-4-1 CSA C22.2 No 60947-4-1 GB/T 14048.4
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-60...80 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.2 cm
Package 1 Width	36.5 cm
Package 1 Length	35.4 cm
Package 1 Weight	3 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

