



Main

Range	TeSys
Device short name	LA9G
Product or component type	Switch module
Quantity per set	Set of 4

Complementary

Product compatibility	LC1G265...330
Accessory / separate part type	Kit
Maximum [I _e] rated operational current	440 A AC-1 ≤ 440 V at 40 °C
Poles description	4P
Connections - terminals	Bolted connection

Environment

Pollution degree	3 conforming to IEC 60947-1
Operating altitude	3000 m without power derating 5000 m with derating factor
Standards	EN/IEC 60947-4-1 UL 60947-4-1 CSA C22.2 No 60947-4-1 GB/T 14048.4
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-60...80 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	16.5 cm
Package 1 Width	26.0 cm
Package 1 Length	21.0 cm
Package 1 Weight	4.5 kg
Unit Type of Package 2	S03
Number of Units in Package 2	2
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	9.6 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

