

# LC1G2654EHEN

High power contactor. TeSys Giga. 4 pole (4NO). AC-1  $\leq 440\text{V}$  385A. standard version. 48...130V wide band AC/DC coil



## Main

Range	TeSys
Range of product	TeSys Giga
Product or component type	Contacteur
Device short name	LC1G
Contacteur application	Power switching
Utilisation category	AC-3 AC-3e AC-1 AC-5a AC-5b AC-6a AC-6b DC-1 DC-3 DC-5
Poles description	4P
[Ue] rated operational voltage	$\leq 1000\text{ V AC } 50/60\text{ Hz}$ $\leq 460\text{ V DC}$
[Ie] rated operational current	265 A (at $\leq 60\text{ }^\circ\text{C}$ ) at $\leq 440\text{ V AC-3}$ 385 A (at $\leq 40\text{ }^\circ\text{C}$ ) at $\leq 1000\text{ V AC-1}$
[Uc] control circuit voltage	48...130 V AC 50/60 Hz 48...130 V DC
Control circuit voltage limits	Operational: 0.8 Uc Min...1.1 Uc Max (at $\leq 60\text{ }^\circ\text{C}$ ) Drop-out: 0.1 Uc Max...0.45 Uc Min (at $\leq 60\text{ }^\circ\text{C}$ )

## Complementary

[Uimp] rated impulse withstand voltage	8 kV
Overtoltage category	III
[Ith] conventional free air thermal current	385 A (at $40\text{ }^\circ\text{C}$ )
Rated breaking capacity	2380 A at 440 V
[Icw] rated short-time withstand current	2.2 KA - 10 s 1.23 KA - 30 s 0.95 KA - 1 min 0.62 KA - 3 min 0.48 kA - 10 min
Associated fuse rating	315 A aM at $\leq 440\text{ V}$ for motor 250 A aM at $\leq 690\text{ V}$ for motor 400 A gG at $\leq 690\text{ V}$
Average impedance	0.000144 Ohm
[Ui] rated insulation voltage	1000 V
Power dissipation per pole	20 W AC-1 - Ith 385 A 11 W AC-3 - Ith 265 A
Compatibility code	LC1G
Pole contact composition	4 NO
Auxiliary contact composition	1 NO + 1 NC
Irms rated making capacity	3320 A at 440 V
Coil technology	Built-in bidirectional peak limiting
Mechanical durability	8 Mcycles
Inrush power in VA (50/60 Hz, AC)	780 VA
Inrush power in W (DC)	695 W

Hold-in power consumption in VA (50/60 Hz, AC)	17.6 VA
Hold-in power consumption in W (DC)	7.8 W
Operating time	40...70 ms closing 15...50 ms opening
Maximum operating rate	600 Cyc/H AC-3 600 Cyc/H AC-3e 300 cyc/h AC-1
Connections - terminals	Power circuit: bar 2 - busbar cross section: 32 x 10 mm Power circuit: lugs-ring terminals 1 185 mm <sup>2</sup> Control circuit: push-in 1 0.2...2.5 mm <sup>2</sup> - cable stiffness: solid stranded without cable end Control circuit: push-in 1 0.25...2.5 mm <sup>2</sup> - cable stiffness: flexible with cable end Control circuit: push-in 2 0.5...1.0 mm <sup>2</sup> with cable end Control circuit: push-in 0.75...2.5 mm <sup>2</sup> - cable stiffness: solid stranded without cable end Control circuit: push-in 0.75...2.5 mm <sup>2</sup> - cable stiffness: flexible with cable end
Connection pitch	45 mm
Mounting support	Plate
Standards	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1 JIS C8201-5-1
Product certifications	CB Scheme[RETURN]CCC[RETURN]cULus[RETURN]EAC[RETURN]CE[RETURN]UKCA[RETURN] RO-MR by DNV-GL
Tightening torque	35 N.m
Height	225 mm
Width	185 mm
Depth	226 mm
Net weight	8.2 kg

## Environment

IP degree of protection	IP2X front face with shrouds conforming to IEC 60529 IP2X front face with shrouds conforming to VDE 0106
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-60...80 °C
Mechanical robustness	Vibrations 5...300 Hz 2 gn contactor open Vibrations 5...300 Hz 4 gn contactor closed Shocks 10 gn 11 ms contactor open Shocks 15 gn 11 ms contactor closed
Colour	Dark grey
Protective treatment	TH
Permissible ambient air temperature around the device	-40...70 °C at U <sub>c</sub>

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	26.0 cm
Package 1 Width	31.0 cm
Package 1 Length	32.0 cm
Package 1 Weight	9.085 kg
Unit Type of Package 2	S06
Number of Units in Package 2	4
Package 2 Height	75 cm
Package 2 Width	60 cm
Package 2 Length	80 cm
Package 2 Weight	46.34 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
PVC free	Yes
Halogen content performance	Halogen free plastic parts product





