



Main

Range	KNX
Product or component type	Gateway with power supply

Complementary

Communication port protocol	BACnet KNX
[Us] rated supply voltage	24 V DC
Power consumption in W	2 W 12 W
LED indicator	LED (green) for CPU load LED (green/red) for KNX powered/reset
Physical interface	1 x RJ45 1 x TP-UART2
Port Ethernet	10BASE-T/100BASE-TX
Control type	RESET push-button
Connections - terminals	KNX bus: bus terminal 1 cable(s) Power supply: 2 screw terminals 1 cable(s) Power supply: screw terminals 1 cable(s)
Mounting support	DIN rail
Height	90 mm
Width	71 mm
Depth	61 mm

Environment

Ambient air temperature for operation	0...45 °C
Operating altitude	<= 2000 m
Relative humidity	0...93 %
IP degree of protection	IP20
Standards	IEC 60950-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.000 cm
Package 1 Width	12.300 cm
Package 1 Length	15.700 cm
Package 1 Weight	229.000 g
Unit Type of Package 2	S03

Number of Units in Package 2	15
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	3.871 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information