



## Main

Product or component type	Mechanical lug
Accessory / separate part type	Connection kit
Poles description	4P

## Complementary

Quantity per set	Set of 1
Location of connection	Downstream Upstream
[In] rated current	15...125 A for copper 15...100 A for aluminium
Conductor material	Steel
Connections - terminals	Screw terminal - 1 cable(s) 2.5...95 mm <sup>2</sup> (AWG 14...AWG 3/0) - solid Screw terminal 2.5...95 mm <sup>2</sup> (AWG 14...AWG 3/0) - stranded Screw terminal 2.5...70 mm <sup>2</sup> (AWG 6...AWG 2/0) - fine stranded
Control wire terminal	10 A for 0.5...6 mm <sup>2</sup> (AWG 20...AWG 10), stranded or fine stranded 10 A for 1.5...6 mm <sup>2</sup> (AWG 20...AWG 10), rigid

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.906 cm
Package 1 Width	35.052 cm
Package 1 Length	52.07 cm
Package 1 Weight	172.365 g
Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Height	10.0 cm
Package 2 Width	35.0 cm
Package 2 Length	52.0 cm
Package 2 Weight	7.307 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free product