



### Main

Range of product	ComPacT NSX100...250 new generation ComPacT NSX100...250
Device short name	VigiPacT
Product or component type	Vigi add-on
Device application	Wiring
Range compatibility	ComPacT new generation ComPacT NSX250 new generation circuit breaker ComPacT ComPacT NSX250 circuit breaker
Poles description	3P
[In] rated current	250 A
Earth-leakage protection class	Class A Class AC
Residual earth-leakage sensitivity adjustment type	Adjustable
Earth-leakage sensitivity	0.03 A for class A 0.1 A for class A 0.3 A for class A 0.5 A for class A 1 A for class A 3 A for class A 10 A for class AC 30 A for class AC
Residual earth-leakage time delay adjustment type	Adjustable
[Δt] residual earth-leakage time delay adjustment	0 Ms 60 Ms 150 Ms 300 Ms 500 Ms 800 Ms 1.2 S 4 s

### Complementary

Network type	AC
Network frequency	50/60 Hz
[Ue] rated operational voltage	200...440 V AC 50/60 Hz conforming to IEC 60947-2
Earth-leakage protection	With
Maximum breaking time	800 ms
Overvoltage category	IV

### Environment

Electrical shock protection class	Class II
Standards	IEC 60947-2

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.5 cm
Package 1 Width	14.0 cm
Package 1 Length	17.5 cm
Package 1 Weight	1.098 kg
Unit Type of Package 2	S04
Number of Units in Package 2	12
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	13.848 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes