



Main

Product or component type	Fuse monitor
Electrical circuit type	Electronic
Device application	Signalling
Accessory / separate part category	Electrical accessory

Complementary

Range compatibility	FuPacT FuPacT ISFT ISFT400 fuse-switch disconnectors
Control type	Handle
[Ue] rated operational voltage	400...690 V AC 50/60 Hz
[Ie] rated operational current	5 A (AC-15) at 200...240 V AC 5 A (AC-15) at 250 V AC 5 A (DC-13) at 24 V DC
Rated breaking capacity	2 kA
Power consumption in VA	3 VA
[Ith] conventional free air thermal current	5 A
[Ui] rated insulation voltage	250 V
Minimum load	10 mA 24 V
Standards	EN 61000-4-5 EN 61000-4-4 ENV 50204 EN 61000-4-6 EN 61000-4-2 EN 55022 EN 61000-4-3
Product certifications	CE
Net weight	0.2 kg

Environment

IP degree of protection	IP20
Pollution degree	3 conforming to IEC 60947-1
Ambient air temperature for operation	-25...55 °C
Ambient air temperature for storage	-40...70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	18.0 cm
Package 1 Width	22.5 cm
Package 1 Length	35.0 cm
Package 1 Weight	1.216 kg
Unit Type of Package 2	S04

Number of Units in Package 2	3
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	4.238 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations