



## Main

Range of product	ISFL160
Range	FuPacT
Product or component type	Block of 1 current transformer
Device application	Power supply
Range compatibility	FuPacT FuPacT ISFL ISFL160 fuse-switch disconnecter
Poles description	3P
Current transformer ratio	150/1 A
Power consumption in VA	2.5 VA

## Complementary

Accessory / separate part category	Measurement accessory
Current transformer type	Measurement class 1
Maximum safety factor	5
[Ue] rated operational voltage	800 V AC 50/60 Hz
IP degree of protection	IP20
Standards	VDE 0414 IEC 60044-1 BS 7626
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...80 °C
Height	328.5 mm
Width	49.5 mm
Depth	30 mm

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.0 cm
Package 1 Width	6.7 cm
Package 1 Length	37.0 cm
Package 1 Weight	271.0 g
Unit Type of Package 2	S04
Number of Units in Package 2	20
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	6.186 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------