



### Main

Range	PrismaSeT
Range of product	PrismaSeT G
Product or component type	Rail
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT PrismaSeT G duct
Type of rail	Modular
Installed device	Acti 9: fixed C120 without earth leakage protection - control: toggle TeSys: fixed GV2LE TeSys: fixed GV2ME TeSys: fixed GV2RTn Acti 9: fixed iC120 without earth leakage protection - control: toggle ComPact: fixed INS100 - control: direct front rotary handle - vertical installation ComPact: fixed INS160 - control: direct front rotary handle - vertical installation ComPact: fixed INS40 - control: direct front rotary handle - vertical installation ComPact: fixed INS63 - control: direct front rotary handle - vertical installation Acti 9: fixed modular device Multi9: fixed modular device Multi9: fixed NG125 without earth leakage protection - control: toggle Multi9: fixed NG125 NA - control: toggle Acti 9: fixed C120 with earth leakage protection - control: toggle Acti 9: fixed iC120 with earth leakage protection - control: toggle Multi9: fixed NG125 with earth leakage protection - control: toggle ComPact: fixed INS125 - control: direct front rotary handle - vertical installation Acti 9: fixed modular device <= 40 A Multi9: fixed modular device <= 40 A
Poles description	1 x 3P: fixed C120 1 x 4P: fixed C120 1 x 3P: fixed iC120 1 x 4P: fixed iC120 1 x 3P: fixed INS100 vertical installation 1 x 4P: fixed INS100 vertical installation 1 x 3P: fixed INS160 vertical installation 1 x 4P: fixed INS160 vertical installation 1 x 3P: fixed INS40 vertical installation 1 x 4P: fixed INS40 vertical installation 1 x 3P: fixed INS63 vertical installation 1 x 4P: fixed INS63 vertical installation 1 x 3P: fixed NG125 1 x 4P: fixed NG125 1 x 3P: fixed NG125 NA 1 x 4P: fixed NG125 NA 1 x 3P: fixed INS125 vertical installation 1 x 4P: fixed INS125 vertical installation 4 x 3P: fixed GV2LE 4 x 3P: fixed GV2ME 4 x 3P: fixed GV2RTn

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Complementary

Installation description	Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm
Number of vertical modules [50 mm]	<p>4 module(s): C120 without earth leakage protection , direct in 300 mm Widefloor-standing duct</p> <p>4 module(s): C120 without earth leakage protection , direct in 300 mm Widewall-mounted duct</p> <p>3 module(s): GV2LE, direct in 300 mm Widefloor-standing duct</p> <p>3 module(s): GV2LE, direct in 300 mm Widewall-mounted duct</p> <p>3 module(s): GV2ME, direct in 300 mm Widefloor-standing duct</p> <p>3 module(s): GV2ME, direct in 300 mm Widewall-mounted duct</p> <p>3 module(s): GV2RTn, direct in 300 mm Widefloor-standing duct</p> <p>3 module(s): GV2RTn, direct in 300 mm Widewall-mounted duct</p> <p>4 module(s): iC120 without earth leakage protection , direct in 300 mm Widefloor-standing duct</p> <p>4 module(s): iC120 without earth leakage protection , direct in 300 mm Widewall-mounted duct</p> <p>4 module(s): INS100, direct in 300 mm Widefloor-standing duct</p> <p>4 module(s): INS100, direct in 300 mm Widewall-mounted duct</p> <p>5 module(s): INS100, direct in 300 mm Widefloor-standing duct</p> <p>5 module(s): INS100, direct in 300 mm Widewall-mounted duct</p> <p>4 module(s): INS125, direct in 300 mm Widefloor-standing duct</p> <p>4 module(s): INS125, direct in 300 mm Widewall-mounted duct</p> <p>5 module(s): INS125, direct in 300 mm Widefloor-standing duct</p> <p>5 module(s): INS125, direct in 300 mm Widewall-mounted duct</p> <p>4 module(s): INS160, direct in 300 mm Widefloor-standing duct</p> <p>4 module(s): INS160, direct in 300 mm Widewall-mounted duct</p> <p>5 module(s): INS160, direct in 300 mm Widefloor-standing duct</p> <p>5 module(s): INS160, direct in 300 mm Widewall-mounted duct</p> <p>4 module(s): INS40, direct in 300 mm Widefloor-standing duct</p> <p>4 module(s): INS40, direct in 300 mm Widewall-mounted duct</p> <p>4 module(s): INS63, direct in 300 mm Widefloor-standing duct</p> <p>4 module(s): INS63, direct in 300 mm Widewall-mounted duct</p> <p>3 module(s): modular device &lt;= 40 A, direct in 300 mm Widefloor-standing duct</p> <p>3 module(s): modular device &lt;= 40 A, direct in 300 mm Widewall-mounted duct</p> <p>4 module(s): modular device, direct in 300 mm Widefloor-standing duct</p> <p>4 module(s): modular device, direct in 300 mm Widewall-mounted duct</p> <p>4 module(s): NG125 without earth leakage protection , direct in 300 mm Widefloor-standing duct</p> <p>4 module(s): NG125 without earth leakage protection , direct in 300 mm Widewall-mounted duct</p> <p>4 module(s): NG125 NA, direct in 300 mm Widefloor-standing duct</p> <p>4 module(s): NG125 NA, direct in 300 mm Widewall-mounted duct</p> <p>4 module(s): C120 with earth leakage protection , direct in 300 mm Widefloor-standing duct</p> <p>4 module(s): C120 with earth leakage protection , direct in 300 mm Widewall-mounted duct</p> <p>4 module(s): iC120 with earth leakage protection , direct in 300 mm Widefloor-standing duct</p> <p>4 module(s): iC120 with earth leakage protection , direct in 300 mm Widewall-mounted duct</p> <p>4 module(s): NG125 with earth leakage protection , direct in 300 mm Widefloor-standing duct</p> <p>4 module(s): NG125 with earth leakage protection , direct in 300 mm Widewall-mounted duct</p>
9 mm pitches	20
Quantity per set	Set of 1
Height	52 mm
Width	218 mm
Depth	100 mm
Net weight	0.14 kg
Colour	Natural
Material	Metal

## Environment

Standards	IEC 61439-1 IEC 61439-2
Product certifications	ASTA

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.2 cm
Package 1 Width	10.5 cm
Package 1 Length	21.8 cm
Package 1 Weight	169.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	13.6 cm
Package 2 Width	21.2 cm
Package 2 Length	25.4 cm
Package 2 Weight	1.861 kg
Unit Type of Package 3	P12
Number of Units in Package 3	300
Package 3 Height	40.0 cm
Package 3 Width	80.0 cm
Package 3 Length	120.0 cm
Package 3 Weight	66.5 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product