

# LVS03011

## W300 ADJUSTABLE MOD. DEV. RAIL

### PRISMA G



#### Main

Range	PrismaSeT
Range of product	PrismaSeT G
Product or component type	Rail
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT PrismaSeT G duct
Type of rail	Adjustable Modular
Installed device	<p>TeSys: fixed GV2L</p> <p>TeSys: fixed GV2P</p> <p>TeSys: fixed GV3</p> <p>ComPact: fixed NG160 without earth leakage protection - control: toggle</p> <p>ComPact: fixed NG160 NA without earth leakage protection - control: toggle</p> <p>Altistart: ATS01N103/106FT</p> <p>TeSys: fixed D or K contactors &lt;= 40 A - horizontal installation</p> <p>TeSys: fixed GV2 + D or K contactors &lt;= 40 A - horizontal installation</p> <p>TeSys: fixed GV3Pxx1 + LC1D40 to D65 - horizontal installation</p> <p>TeSys: fixed TeSys U - horizontal installation</p> <p>ComPact: fixed NSXm without earth leakage protection - control: toggle - vertical installation</p> <p>ComPact: fixed NSXm with earth leakage protection - control: toggle - vertical installation</p>
Poles description	<p>1 x 3P: fixed NG160</p> <p>1 x 4P: fixed NG160</p> <p>1 x 3P: fixed NG160 NA</p> <p>1 x 4P: fixed NG160 NA</p> <p>4 x 4P: fixed D or K contactors &lt;= 40 A horizontal installation</p> <p>4 x 3P: fixed GV2 + D or K contactors &lt;= 40 A horizontal installation</p> <p>4 x 3P: fixed GV2L</p> <p>4 x 3P: fixed GV2P</p> <p>3 x 3P: fixed GV3</p> <p>3 x 3P: fixed GV3Pxx1 + LC1D40 to D65 horizontal installation</p> <p>4 x 3P: fixed TeSys U horizontal installation</p> <p>1 x 3P or 4P: fixed NSXm vertical installation</p>

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Complementary

Installation description	Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm
Number of vertical modules [50 mm]	4 module(s): ATS01N103/106FT in 300 mm Widefloor-standing duct 4 module(s): ATS01N103/106FT in 300 mm Widewall-mounted duct 3 module(s): D or K contactors <= 40 A, direct in 300 mm Widefloor-standing duct 3 module(s): D or K contactors <= 40 A, direct in 300 mm Widewall-mounted duct 5 module(s): GV2 + D or K contactors <= 40 A, direct in 300 mm Widefloor-standing duct 5 module(s): GV2 + D or K contactors <= 40 A, direct in 300 mm Widewall-mounted duct 3 module(s): GV2L, direct in 300 mm Widefloor-standing duct 3 module(s): GV2L, direct in 300 mm Widewall-mounted duct 3 module(s): GV2P, direct in 300 mm Widefloor-standing duct 3 module(s): GV2P, direct in 300 mm Widewall-mounted duct 5 module(s): GV3, direct in 300 mm Widefloor-standing duct 5 module(s): GV3, direct in 300 mm Widewall-mounted duct 7 module(s): GV3Pxx1 + LC1D40 to D65, direct in 300 mm Widefloor-standing duct 7 module(s): GV3Pxx1 + LC1D40 to D65, direct in 300 mm Widewall-mounted duct 5 module(s): NG160 without earth leakage protection , direct in 300 mm Widefloor-standing duct 5 module(s): NG160 without earth leakage protection , direct in 300 mm Widewall-mounted duct 5 module(s): NG160 NA without earth leakage protection , direct in 300 mm Widefloor-standing duct 5 module(s): NG160 NA without earth leakage protection , direct in 300 mm Widewall-mounted duct 7 module(s): NSXm without earth leakage protection , direct in 300 mm Widefloor-standing duct 7 module(s): NSXm without earth leakage protection , direct in 300 mm Widewall-mounted duct 7 module(s): NSXm without earth leakage protection , connection block in 300 mm Widefloor-standing duct 7 module(s): NSXm without earth leakage protection , connection block in 300 mm Widewall-mounted duct 5 module(s): TeSys U, direct in 300 mm Widefloor-standing duct 5 module(s): TeSys U, direct in 300 mm Widewall-mounted duct 4 module(s): TeSys U, direct in 300 mm Widefloor-standing duct 4 module(s): TeSys U, direct in 300 mm Widewall-mounted duct 7 module(s): NSXm with earth leakage protection , direct in 300 mm Widefloor-standing duct 7 module(s): NSXm with earth leakage protection , direct in 300 mm Widewall-mounted duct 7 module(s): NSXm with earth leakage protection , connection block in 300 mm Widefloor-standing duct 7 module(s): NSXm with earth leakage protection , connection block in 300 mm Widewall-mounted duct
9 mm pitches	20
Quantity per set	Set of 1
Height	58 mm
Width	217 mm
Depth	97 mm
Net weight	0.18 kg
Colour	Natural
Material	Metal

## Environment

Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASTA

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.5 cm
Package 1 Width	5.7 cm
Package 1 Length	21.6 cm
Package 1 Weight	242.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	15.0 cm
Package 2 Width	23.2 cm
Package 2 Length	30.4 cm
Package 2 Weight	2.576 kg
Unit Type of Package 3	P12
Number of Units in Package 3	130
Package 3 Height	28.0 cm
Package 3 Width	80.0 cm
Package 3 Length	120.0 cm
Package 3 Weight	44.5 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 <a href="#">Yes</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product