

LVS03154

Mounting plate, PrismaSeT G, Insulating type, class 2, for kilowatt-hour meters, W600/W651mm



Main

Range	PrismaSeT
Range of product	PrismaSeT G PrismaSeT P
Product or component type	Insulating plate
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT PrismaSeT G enclosure PrismaSeT PrismaSeT P cubicle
Installation description	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Cubicle - width 650 mm depth 400 mm Pack enclosure - width 555 mm
Installed device	Power meters: kilowatt-hour meters - vertical installation
Poles description	2 x 4P: kilowatt-hour meters vertical installation 3 x 2P: kilowatt-hour meters vertical installation
Number of vertical modules [50 mm]	9 module(s): kilowatt-hour meters in 600 mm Widefloor-standing enclosure 9 module(s): kilowatt-hour meters in 600 mm Widewall-mounted enclosure 9 module(s): kilowatt-hour meters in 650 mm Widecubicle 9 module(s): kilowatt-hour meters in 555 mm WidePack enclosure 6 module(s): kilowatt-hour meters in 600 mm Widefloor-standing enclosure 6 module(s): kilowatt-hour meters in 600 mm Widewall-mounted enclosure 6 module(s): kilowatt-hour meters in 650 mm Widecubicle 6 module(s): kilowatt-hour meters in 555 mm WidePack enclosure
Standards	IEC 61439-2
Product certifications	ASTA

Complementary

Material	Sheet steel
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Surface finish	Matt Textured
Colour	White (RAL 9003)
Width	600 mm
Height	420 mm

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Net weight	0.66 kg
Functional unit	600 mm PrismaSeT G floor-standing enclosure power meters kilowatt-hour meters vertical 2P 3 6 600 mm PrismaSeT G wall-mounted enclosure power meters kilowatt-hour meters vertical 2P 3 6 600 mm PrismaSeT G floor-standing enclosure power meters kilowatt-hour meters vertical 4P 2 9 600 mm PrismaSeT G wall-mounted enclosure power meters kilowatt-hour meters vertical 4P 2 9 650 mm 400 mm PrismaSeT P cubicle power meters kilowatt-hour meters vertical 2P 3 6 650 mm 400 mm PrismaSeT P cubicle power meters kilowatt-hour meters vertical 4P 2 9

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.0 cm
Package 1 Width	52.0 cm
Package 1 Length	67.8 cm
Package 1 Weight	633.0 g
Unit Type of Package 2	P12
Number of Units in Package 2	24
Package 2 Height	73.0 cm
Package 2 Width	80.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	28.5 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product