LVS03287 FRONT PLATE INS630 HZ W850 6M





Main

Range	PrismaSeT
Range of product	PrismaSeT G
Product or component type	Front plate
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT PrismaSeT G enclosure
Type of front plate	Cut-out
Installed device	ComPact: fixed INS320400 - control: direct front rotary handle - horizontal installation ComPact: fixed INS500630 - control: direct front rotary handle - horizontal installation ComPact: fixed INV320400 - control: direct front rotary handle - horizontal installation ComPact: fixed INV500630 - control: direct front rotary handle - horizontal installation
Poles description	1 x 3P: mounting plate support: INS320400 horizontal installation 1 x 4P: mounting plate support: INS320400 horizontal installation 1 x 3P: mounting plate support: INS500630 horizontal installation 1 x 4P: mounting plate support: INS500630 horizontal installation 1 x 3P: mounting plate support: INV320400 horizontal installation 1 x 4P: mounting plate support: INV320400 horizontal installation 1 x 3P: mounting plate support: INV500630 horizontal installation 1 x 4P: mounting plate support: INV500630 horizontal installation 1 x 4P: mounting plate support: INV500630 horizontal installation
Operating position	Horizontal

Complementary

Enclosure/cubicle description	Floor-standing enclosure - width 850 mm	
Connection position	Connection block	
Number of vertical modules [50 mm]	6	
Standards	IEC 61439-2 IEC 61439-1	
Product certifications	ASTA	
Surface finish	Matt Textured	
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder	
Colour	White (RAL 9003)	
Height	300 mm	
Width	850 mm	
Net weight	1.94 kg	

Quantity per set	Set of 1
Functional unit	850 mm PrismaSeT G floor-standing enclosure ComPact INS320400 fixed

direct front rotary handle horizontal 3P 1 direct with long terminal shield 9 850 mm PrismaSeT G floor-standing enclosure ComPact INS320...400 fixed direct front rotary handle horizontal 4P 1 direct with long terminal shield 9 850 mm PrismaSeT G floor-standing enclosure ComPact INS320...400 fixed direct front rotary handle horizontal 3P 1 direct with long terminal shield 6 850 mm PrismaSeT G floor-standing enclosure ComPact INS320...400 fixed direct front rotary handle horizontal 4P 1 direct with long terminal shield 6 850 mm PrismaSeT G floor-standing enclosure ComPact INS500...630 fixed direct front rotary handle horizontal 3P 1 direct with long terminal shield 9 850 mm PrismaSeT G floor-standing enclosure ComPact INS500...630 fixed direct front rotary handle horizontal 4P 1 direct with long terminal shield 9 850 mm PrismaSeT G floor-standing enclosure ComPact INS500...630 fixed direct front rotary handle horizontal 3P 1 direct with long terminal shield 6 850 mm PrismaSeT G floor-standing enclosure ComPact INS500...630 fixed direct front rotary handle horizontal 4P 1 direct with long terminal shield 6 850 mm PrismaSeT G floor-standing enclosure ComPact INV320...400 fixed direct front rotary handle horizontal 3P 1 direct with long terminal shield 9 850 mm PrismaSeT G floor-standing enclosure ComPact INV320...400 fixed direct front rotary handle horizontal 4P 1 direct with long terminal shield 9 850 mm PrismaSeT G floor-standing enclosure ComPact INV320...400 fixed direct front rotary handle horizontal 3P 1 direct with long terminal shield 6 850 mm PrismaSeT G floor-standing enclosure ComPact INV320...400 fixed direct front rotary handle horizontal 4P 1 direct with long terminal shield 6 850 mm PrismaSeT G floor-standing enclosure ComPact INV500...630 fixed direct front rotary handle horizontal 3P 1 direct with long terminal shield 9 850 mm PrismaSeT G floor-standing enclosure ComPact INV500...630 fixed direct front rotary handle horizontal 4P 1 direct with long terminal shield 9 850 mm PrismaSeT G floor-standing enclosure ComPact INV500...630 fixed direct front rotary handle horizontal 3P 1 direct with long terminal shield 6 850 mm PrismaSeT G floor-standing enclosure ComPact INV500...630 fixed direct front rotary handle horizontal 4P 1 direct with long terminal shield 6

Environment

IP degree of protection	IP30	
ii degree or protection	11 30	

Packing Units

PCE 1 3.0 cm 30.0 cm 75.0 cm 1.926 kg
3.0 cm 30.0 cm 75.0 cm 1.926 kg
30.0 cm 75.0 cm 1.926 kg
75.0 cm 1.926 kg
1.926 kg
201
BB1
4
7.0 cm
32.0 cm
78.5 cm
8.1 kg
P12
40
48.0 cm
80.0 cm
120.0 cm
92.5 kg

Offer Sustainability

Toxic heavy metal free	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
REACh free of SVHC	Yes	
REACh Regulation	REACh Declaration	
Sustainable offer status	Green Premium product	

Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₽	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	
PVC free	Yes	
Halogen content performance	Halogen free plastic parts product	