



### Main

Range	PrismaSeT
Range of product	PrismaSeT P
Product or component type	Rail
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT PrismaSeT P
Type of rail	Adjustable Modular
Installed device	<p>TeSys: fixed GV2L                      TeSys: fixed GV2P                      TeSys: fixed GV3                      ComPact: fixed NG160 without earth leakage protection - control: toggle                      ComPact: fixed NG160 NA without earth leakage protection - control: toggle                      ComPact: fixed NG160 with earth leakage protection - control: toggle                      Altistart: ATS01N                      Altistart: ATS01N103/106FT                      TeSys: fixed D or K contactors &lt;= 40 A - horizontal installation                      TeSys: fixed GV2 + D or K contactors &lt;= 40 A - horizontal installation                      TeSys: fixed TeSys U - horizontal installation                      PowerLogic: PM5500                      PowerLogic: iEM3000                      PowerLogic: PM3000                      PowerLogic: PM5563RD                      ComPact: fixed NSXm without earth leakage protection - control: toggle - vertical installation                      ComPact: fixed NSXm with earth leakage protection - control: toggle - vertical installation</p>
Poles description	<p>9 x 3P: fixed GV2L                      9 x 3P: fixed GV2P                      7 x 3P: fixed GV3                      1 x 3P: fixed NG160                      1 x 4P: fixed NG160                      1 x 3P: fixed NG160 NA                      1 x 4P: fixed NG160 NA                      9 x 4P: fixed D or K contactors &lt;= 40 A horizontal installation                      9 x 3P: fixed GV2 + D or K contactors &lt;= 40 A horizontal installation                      9 x 3P: fixed TeSys U horizontal installation                      1 x 3P or 4P: fixed NSXm vertical installation</p>

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Complementary

Installation description	Cubicle - width 650 mm depth 400 mm
Enclosure nominal height	2000 mm
Number of vertical modules [50 mm]	5 module(s): ATS01N in 650 mm Widecubicle 6 module(s): ATS01N in 650 mm Widecubicle 4 module(s): ATS01N103/106FT in 650 mm Widecubicle 3 module(s): D or K contactors <= 40 A, direct in 650 mm Widecubicle 5 module(s): GV2 + D or K contactors <= 40 A, direct in 650 mm Widecubicle 3 module(s): GV2L, direct in 650 mm Widecubicle 3 module(s): GV2P, direct in 650 mm Widecubicle 5 module(s): GV3, direct in 650 mm Widecubicle 4 module(s): iEM3000 in 650 mm Widecubicle 5 module(s): NG160 without earth leakage protection , direct in 650 mm Widecubicle 5 module(s): NG160 NA without earth leakage protection , direct in 650 mm Widecubicle 8 module(s): NSXm without earth leakage protection , direct in 650 mm Widecubicle 4 module(s): PM3000 in 650 mm Widecubicle 3 module(s): PM5500 in 650 mm Widecubicle 3 module(s): PM5563RD in 650 mm Widecubicle 5 module(s): TeSys U, direct in 650 mm Widecubicle 4 module(s): TeSys U, direct in 650 mm Widecubicle 5 module(s): NG160 with earth leakage protection , direct in 650 mm Widecubicle 8 module(s): NSXm with earth leakage protection , direct in 650 mm Widecubicle
9 mm pitches	48
Quantity per set	Set of 1
Height	30 mm
Width	563 mm
Depth	325 mm
Net weight	0.86 kg
Colour	Natural
Material	Metal

## Environment

Standards	IEC 61439-1 IEC 61439-2
Product certifications	ASTA

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.000 cm
Package 1 Width	4.500 cm
Package 1 Length	52.000 cm
Package 1 Weight	817.000 g
Unit Type of Package 2	S04
Number of Units in Package 2	20
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	17.138 kg
Unit Type of Package 3	P12
Number of Units in Package 3	160
Package 3 Height	73.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	153.000 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product