


LVS03420

Mounting plate, PrismaSeT P, 3 to 4 devices
NS-INS250 Toggle vertically fixed, enclosure
W650mm





Main

Range	PrismaSeT
Range of product	PrismaSeT P
Product or component type	Mounting plate
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT PrismaSeT P cubicle
Installation description	Cubicle - width 650 mm depth 400 mm
Installed device	<p>EasyPact: fixed CVS100...160 without earth leakage protection - control: toggle - vertical installation</p> <p>EasyPact: fixed CVS250 without earth leakage protection - control: toggle - vertical installation</p> <p>ComPact: fixed INS250 - control: direct front rotary handle - vertical installation</p> <p>ComPact: fixed INV250 - control: direct front rotary handle - vertical installation</p> <p>ComPact: fixed NSX100...160 without earth leakage protection - control: toggle - vertical installation</p> <p>ComPact: fixed NSX250 without earth leakage protection - control: toggle - vertical installation</p> <p>EasyPact: fixed CVS100...160 with earth leakage protection - control: toggle - vertical installation</p> <p>EasyPact: fixed CVS250 with earth leakage protection - control: toggle - vertical installation</p> <p>ComPact: fixed NSX100...160 with earth leakage protection - control: toggle - vertical installation</p> <p>ComPact: fixed NSX250 with earth leakage protection - control: toggle - vertical installation</p>
Poles description	<p>1 x 3P: fixed INS250 vertical installation</p> <p>1 x 4P: fixed INS250 vertical installation</p> <p>1 x 3P: fixed INV250 vertical installation</p> <p>1 x 4P: fixed INV250 vertical installation</p> <p>4 x 3P: fixed CVS100...160 vertical installation</p> <p>3 x 4P: fixed CVS100...160 vertical installation</p> <p>4 x 3P: fixed CVS250 vertical installation</p> <p>3 x 4P: fixed CVS250 vertical installation</p> <p>4 x 3P: fixed NSX100...160 vertical installation</p> <p>3 x 4P: fixed NSX100...160 vertical installation</p> <p>4 x 3P: fixed NSX250 vertical installation</p> <p>3 x 4P: fixed NSX250 vertical installation</p> <p>3 x 3P: fixed INS250 vertical installation</p> <p>2 x 4P: fixed INS250 vertical installation</p> <p>3 x 3P: fixed INV250 vertical installation</p> <p>2 x 4P: fixed INV250 vertical installation</p>

Number of vertical modules [50 mm]	<p>9 module(s): CVS100...160 without earth leakage protection , direct in 650 mm Widecubicle</p> <p>9 module(s): CVS250 without earth leakage protection , direct in 650 mm Widecubicle</p> <p>7 module(s): INS250, Linergy FC in 650 mm Widecubicle</p> <p>9 module(s): INS250, direct in 650 mm Widecubicle</p> <p>7 module(s): INV250, Linergy FC in 650 mm Widecubicle</p> <p>9 module(s): INV250, direct in 650 mm Widecubicle</p> <p>6 module(s): NSX100...160 without earth leakage protection , Linergy FC in 650 mm Widecubicle</p> <p>8 module(s): NSX100...160 without earth leakage protection , direct in 650 mm Widecubicle</p> <p>7 module(s): NSX250 without earth leakage protection , Linergy FC in 650 mm Widecubicle</p> <p>9 module(s): NSX250 without earth leakage protection , direct in 650 mm Widecubicle</p> <p>11 module(s): CVS100...160 with earth leakage protection , direct in 650 mm Widecubicle</p> <p>11 module(s): CVS250 with earth leakage protection , direct in 650 mm Widecubicle</p> <p>8 module(s): NSX100...160 with earth leakage protection , Linergy FC in 650 mm Widecubicle</p> <p>10 module(s): NSX100...160 with earth leakage protection , direct in 650 mm Widecubicle</p> <p>9 module(s): NSX250 with earth leakage protection , Linergy FC in 650 mm Widecubicle</p> <p>11 module(s): NSX250 with earth leakage protection , direct in 650 mm Widecubicle</p>
Standards	IEC 61439-2
Product certifications	ASTA

Complementary

Material	Sheet steel
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Surface finish	Matt Textured
Colour	White (RAL 9003)
Width	593 mm
Height	152 mm
Depth	136 mm

Net weight	1.28 kg
Functional unit	650 mm 400 mm PrismaSeT P cubicle EasyPact CVS100...160 without fixed toggle vertical 3P 4 direct 9 162.5 mm 650 mm 400 mm PrismaSeT P cubicle EasyPact CVS100...160 without fixed toggle vertical 4P 3 direct 9 162.5 mm 650 mm 400 mm PrismaSeT P cubicle EasyPact CVS250 without fixed toggle vertical 3P 4 direct 9 162.5 mm 650 mm 400 mm PrismaSeT P cubicle EasyPact CVS250 without fixed toggle vertical 4P 3 direct 9 162.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact INS250 fixed direct front rotary handle vertical 3P 1 Linergy FC 7 112.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact INS250 fixed direct front rotary handle vertical 3P 3 Linergy FC 7 112.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact INS250 fixed direct front rotary handle vertical 4P 1 Linergy FC 7 112.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact INS250 fixed direct front rotary handle vertical 4P 2 Linergy FC 7 112.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact INS250 fixed direct front rotary handle vertical 3P 1 direct 9 212.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact INS250 fixed direct front rotary handle vertical 4P 1 direct 9 212.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact INS250 fixed direct front rotary handle vertical 3P 3 direct 9 212.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact INS250 fixed direct front rotary handle vertical 4P 2 direct 9 212.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact INV250 fixed direct front rotary handle vertical 3P 1 Linergy FC 7 112.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact INV250 fixed direct front rotary handle vertical 3P 3 Linergy FC 7 112.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact INV250 fixed direct front rotary handle vertical 4P 1 Linergy FC 7 112.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact INV250 fixed direct front rotary handle vertical 4P 2 Linergy FC 7 112.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact INV250 fixed direct front rotary handle vertical 3P 1 direct 9 212.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact INV250 fixed direct front rotary handle vertical 3P 3 direct 9 212.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact INV250 fixed direct front rotary handle vertical 4P 2 direct 9 212.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX100...160 without fixed toggle vertical 3P 4 Linergy FC 6 62.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX100...160 without fixed toggle vertical 4P 3 Linergy FC 6 62.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX100...160 without fixed toggle vertical 3P 4 direct 8 162.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX100...160 without fixed toggle vertical 4P 3 direct 8 162.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed toggle vertical 3P 4 Linergy FC 7 62.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 with fixed toggle vertical 3P 4 direct 11 162.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 with fixed toggle vertical 4P 3 direct 11 162.5 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.400 cm
Package 1 Width	15.100 cm
Package 1 Length	58.800 cm
Package 1 Weight	1.541 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	5
Package 2 Height	17.000 cm
Package 2 Width	33.500 cm
Package 2 Length	61.500 cm
Package 2 Weight	8.101 kg
Unit Type of Package 3	P12
Number of Units in Package 3	80
Package 3 Height	80.000 cm

Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	142.500 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product