





## Main

Range	PrismaSeT
Range of product	PrismaSeT P
Product or component type	Mounting plate
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT PrismaSeT P cubicle
Installation description	Cubicle - width 400 mm depth 400 mm
Installed device	<p>ComPact: fixed NSX400 without earth leakage protection - control: toggle - vertical installation</p> <p>ComPact: fixed NSX630 without earth leakage protection - control: toggle - vertical installation</p> <p>ComPact: fixed NSX400 with earth leakage protection - control: toggle - vertical installation</p> <p>ComPact: fixed NSX630 with earth leakage protection - control: toggle - vertical installation</p> <p>ComPact: fixed NSX400 without earth leakage protection - control: direct front rotary handle - vertical installation</p> <p>ComPact: fixed NSX630 without earth leakage protection - control: direct front rotary handle - vertical installation</p> <p>ComPact: plug-in NSX400 without earth leakage protection - control: toggle - vertical installation</p> <p>ComPact: fixed NSX400 without earth leakage protection - control: motor mechanism - vertical installation</p> <p>ComPact: plug-in NSX400 without earth leakage protection - control: direct front rotary handle - vertical installation</p> <p>ComPact: plug-in NSX400 without earth leakage protection - control: motor mechanism - vertical installation</p> <p>ComPact: plug-in NSX630 without earth leakage protection - control: toggle - vertical installation</p> <p>ComPact: fixed NSX630 without earth leakage protection - control: motor mechanism - vertical installation</p> <p>ComPact: plug-in NSX630 without earth leakage protection - control: direct front rotary handle - vertical installation</p> <p>ComPact: plug-in NSX630 without earth leakage protection - control: motor mechanism - vertical installation</p> <p>ComPact: plug-in NSX400 with earth leakage protection - control: toggle - vertical installation</p> <p>ComPact: plug-in NSX630 with earth leakage protection - control: toggle - vertical installation</p> <p>ComPact: fixed NS1250 - control: toggle - vertical installation</p> <p>ComPact: fixed NS1250 - control: direct front rotary handle - vertical installation</p> <p>ComPact: fixed NS1250 - control: motor mechanism - vertical installation</p> <p>ComPact: fixed NS1600 - control: toggle - vertical installation</p> <p>ComPact: fixed NS1600 - control: direct front rotary handle - vertical installation</p> <p>ComPact: fixed NS1600 - control: motor mechanism - vertical installation</p> <p>ComPact: fixed NS630b...1000 - control: toggle - vertical installation</p> <p>ComPact: fixed NS630b...1000 - control: direct front rotary handle - vertical installation</p> <p>ComPact: fixed NS630b...1000 - control: motor mechanism - vertical installation</p>

Poles description	1 x 3P: fixed NSX400 vertical installation 1 x 4P: fixed NSX400 vertical installation 1 x 3P: fixed NSX630 vertical installation 1 x 4P: fixed NSX630 vertical installation 1 x 3P: plug-in NSX400 vertical installation 1 x 4P: plug-in NSX400 vertical installation 1 x 3P: plug-in NSX630 vertical installation 1 x 4P: plug-in NSX630 vertical installation 1 x 3P: fixed NS1250 vertical installation 1 x 4P: fixed NS1250 vertical installation 1 x 3P: fixed NS1600 vertical installation 1 x 4P: fixed NS1600 vertical installation 1 x 3P: fixed NS630b...1000 vertical installation 1 x 4P: fixed NS630b...1000 vertical installation
Number of vertical modules [50 mm]	36 module(s): NS1250, direct in 400 mm Widecubicle 36 module(s): NS1600, direct in 400 mm Widecubicle 36 module(s): NS630b...1000, direct in 400 mm Widecubicle 12 module(s): NSX400 without earth leakage protection , front connection in 400 mm Widecubicle 12 module(s): NSX630 without earth leakage protection , front connection in 400 mm Widecubicle 14 module(s): NSX400 with earth leakage protection , front connection in 400 mm Widecubicle 14 module(s): NSX630 with earth leakage protection , front connection in 400 mm Widecubicle
Standards	IEC 61439-2
Product certifications	ASTA

### Complementary

Material	Sheet steel
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Surface finish	Matt Textured
Colour	White (RAL 9003)
Width	400 mm
Height	300 mm





## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.000 cm
Package 1 Width	31.000 cm
Package 1 Length	37.500 cm
Package 1 Weight	2.878 kg
Unit Type of Package 2	S04
Number of Units in Package 2	4
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	12.600 kg
Unit Type of Package 3	P12
Number of Units in Package 3	96
Package 3 Height	105.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	319.000 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product