



Main

Range	PrismaSeT
Range of product	PrismaSeT P
Product or component type	Mounting plate
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT PrismaSeT P cubicle
Installation description	Cubicle - width 650 mm depth 400 mm
Mounting plate description	Busbar
Installed device	FuPact: fixed ISFL160 - control: fuse carriers handle - vertical installation
Poles description	9 x 3P: fixed ISFL160 vertical installation
Number of vertical modules [50 mm]	11 module(s): ISFL160, rear connection on busbar in 650 mm Widecubicle
Standards	IEC 61439-2
Product certifications	ASTA

Complementary

Connections - terminals	Cable ISFL160 bottom 87.5 mm Cable ISFL160 top 62.5 mm
Material	Sheet steel
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Surface finish	Matt Textured
Colour	White (RAL 9003)
Width	70 mm
Height	625 mm
Depth	365 mm
Net weight	2.44 kg
Functional unit	650 mm 400 mm PrismaSeT P cubicle FuPact ISFL160 fixed fuse carriers handle vertical 3P 9 rear connection on busbar 11 0.2 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.5 cm
Package 1 Width	8.0 cm
Package 1 Length	43.5 cm
Package 1 Weight	2.483 kg
Unit Type of Package 2	P12
Number of Units in Package 2	22
Package 2 Height	19.0 cm
Package 2 Width	80.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	66.0 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product