



Main

| | |
|------------------------------------|--|
| Range | PrismaSeT |
| Range of product | PrismaSeT P |
| Product or component type | Front plate |
| Accessory / separate part category | Installation accessory |
| Range compatibility | PrismaSeT PrismaSeT P cubicle |
| Type of front plate | Cut-out |
| Installed device | ComPact: fixed INS250 - control: direct front rotary handle - horizontal installation ComPact: fixed INV250 - control: direct front rotary handle - horizontal installation |
| Poles description | 1 x 3P: mounting plate support: INS250 horizontal installation 1 x 4P: mounting plate support: INS250 horizontal installation 1 x 3P: mounting plate support: INV250 horizontal installation 1 x 4P: mounting plate support: INV250 horizontal installation |
| Operating position | Horizontal |

Complementary

| | |
|------------------------------------|--|
| Enclosure/cubicle description | Cubicle - width 650 mm depth 400 mm |
| Connection position | Direct connection |
| Number of vertical modules [50 mm] | 4 |
| Standards | IEC 61439-2 IEC 61439-1 |
| Product certifications | ASTA |
| Material | Steel |
| Surface finish | Textured Matt |
| Protective treatment | Electrophoresis treatment and hot-polymerised polyester epoxy powder |
| Colour | White (RAL 9003) |
| Height | 200 mm |
| Width | 500 mm |
| Net weight | 0.82 kg |
| Quantity per set | Set of 1 |
| Functional unit | 650 mm 400 mm PrismaSeT P cubicle ComPact INS250 fixed direct front rotary handle horizontal 3P 1 direct 4 650 mm 400 mm PrismaSeT P cubicle ComPact INS250 fixed direct front rotary handle horizontal 4P 1 direct 4 650 mm 400 mm PrismaSeT P cubicle ComPact INV250 fixed direct front rotary handle horizontal 3P 1 direct 4 650 mm 400 mm PrismaSeT P cubicle ComPact INV250 fixed direct front rotary handle horizontal 4P 1 direct 4 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 3 cm |
| Package 1 Width | 21.5 cm |
| Package 1 Length | 51.5 cm |
| Package 1 Weight | 789 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 16 cm |
| Package 2 Width | 22.5 cm |
| Package 2 Length | 53 cm |
| Package 2 Weight | 8.05 kg |
| Unit Type of Package 3 | P12 |
| Number of Units in Package 3 | 180 |
| Package 3 Height | 58 cm |
| Package 3 Width | 80 cm |
| Package 3 Length | 120 cm |
| Package 3 Weight | 156 kg |

Offer Sustainability

| | |
|-----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation |  China RoHS Declaration |
| RoHS exemption information |  Yes |
| Environmental Disclosure |  Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| PVC free | Yes |
| Halogen content performance | Halogen free plastic parts product |