


LVS03904

Front plate, PrismaSeT P and G, for Power meter 96x96 4No's/vigirex 72x72 5No's with cut out, 3M, W600, white, RAL 9003



Main

Range	PrismaSeT
Range of product	PrismaSeT G PrismaSeT P
Product or component type	Front plate
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT PrismaSeT G enclosure PrismaSeT PrismaSeT P cubicle
Type of front plate	Cut-out
Type of front plate	Cut-out
Installed device	Vigirex: RH10 Vigirex: RH21 Vigirex: RH99 Human-switchboard interface: 72 x 72 mm device Human-switchboard interface: 96 x 96 mm device Human-switchboard interface: HSI PowerLogic: PM400...800 Enerlin'X: FDM121

Complementary

Enclosure/cubicle description	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Cubicle - width 650 mm depth 400 mm
Number of vertical modules [50 mm]	3
Standards	IEC 61439-1 IEC 61439-2
Product certifications	ASTA
Material	Steel
Surface finish	Matt Textured
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White (RAL 9003)
Height	150 mm
Width	500 mm
Net weight	0.32 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Quantity per set	Set of 1
Functional unit	600 mm PrismaSeT G floor-standing enclosure human-switchboard interface 72 x 72 mm device 5 3 600 mm PrismaSeT G wall-mounted enclosure human-switchboard interface 72 x 72 mm device 5 3 650 mm 400 mm PrismaSeT P cubicle human-switchboard interface 72 x 72 mm device 5 3 600 mm PrismaSeT G floor-standing enclosure human-switchboard interface 96 x 96 mm device 4 3 600 mm PrismaSeT G wall-mounted enclosure human-switchboard interface 96 x 96 mm device 4 3 650 mm 400 mm PrismaSeT P cubicle human-switchboard interface 96 x 96 mm device 4 3 600 mm PrismaSeT G floor-standing enclosure human-switchboard interface HSI 5 3 600 mm PrismaSeT G wall-mounted enclosure human-switchboard interface HSI 5 3 600 mm PrismaSeT G floor-standing enclosure human-switchboard interface HSI 4 3 600 mm PrismaSeT G wall-mounted enclosure human-switchboard interface HSI 4 3 650 mm 400 mm PrismaSeT P cubicle human-switchboard interface HSI 5 3 650 mm 400 mm PrismaSeT P cubicle human-switchboard interface HSI 4 3 600 mm PrismaSeT G floor-standing enclosure PowerLogic 4 3 600 mm PrismaSeT G wall-mounted enclosure PowerLogic 4 3 650 mm 400 mm PrismaSeT P cubicle PowerLogic 4 3 600 mm PrismaSeT G floor-standing enclosure Vigirex 5 3 600 mm PrismaSeT G wall-mounted enclosure Vigirex 5 3 650 mm 400 mm PrismaSeT P cubicle Vigirex 5 3 600 mm PrismaSeT G floor-standing enclosure Enerlin'X FDM121 4 3 600 mm PrismaSeT G wall-mounted enclosure Enerlin'X FDM121 4 3 650 mm 400 mm PrismaSeT P cubicle Enerlin'X FDM121 4 3

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.0 cm
Package 1 Width	15.0 cm
Package 1 Length	50.0 cm
Package 1 Weight	340.0 g
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	20.0 cm
Package 2 Width	39.0 cm
Package 2 Length	59.0 cm
Package 2 Weight	4.14 kg
Unit Type of Package 3	P12
Number of Units in Package 3	40
Package 3 Height	33.0 cm
Package 3 Width	80.0 cm
Package 3 Length	120.0 cm
Package 3 Weight	29.0 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes

Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product
