

LVS03908

Mounting plate, PrismaSeT P, for support
96x96 metering dev/push-button for cut-out
front plate 03911/03913



Main

Range	PrismaSeT
Range of product	PrismaSeT P PrismaSeT G
Product or component type	Mounting plate
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT PrismaSeT G enclosure PrismaSeT PrismaSeT P cubicle
Installation description	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Floor-standing enclosure - width 850 mm Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm Cubicle - width 400 mm depth 400 mm Cubicle - width 650 mm depth 400 mm Cubicle duct - width 300 mm depth 400 mm
Mounting plate description	Plain
Installed device	Human-switchboard interface: HSI
Number of vertical modules [50 mm]	3 module(s): HSI in 600 mm Widefloor-standing enclosure 3 module(s): HSI in 600 mm Widewall-mounted enclosure 3 module(s): HSI in 650 mm Widecubicle 3 module(s): HSI in 300 mm Widecubicle duct 3 module(s): HSI in 400 mm Widecubicle 4 module(s): HSI in 850 mm Widefloor-standing enclosure 3 module(s): HSI in 300 mm Widefloor-standing duct 3 module(s): HSI in 300 mm Widewall-mounted duct 3 module(s): HSI in 850 mm Widefloor-standing enclosure
Standards	IEC 61439-2
Product certifications	ASTA

Complementary

Material	Plastic
Colour	White (RAL 9001)
Width	96 mm
Height	96 mm
Depth	21 mm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Net weight	0.04 kg
Functional unit	600 mm PrismaSeT G floor-standing enclosure human-switchboard interface HSI 4 3 600 mm PrismaSeT G wall-mounted enclosure human-switchboard interface HSI 4 3 650 mm 400 mm PrismaSeT P cubicle human-switchboard interface HSI 4 3 300 mm 400 mm PrismaSeT P cubicle duct human-switchboard interface HSI 4 3 400 mm 400 mm PrismaSeT P cubicle human-switchboard interface HSI 4 3 850 mm PrismaSeT G floor-standing enclosure human-switchboard interface HSI 1 4 600 mm PrismaSeT G floor-standing enclosure human-switchboard interface HSI 1 3 600 mm PrismaSeT G wall-mounted enclosure human-switchboard interface HSI 1 3 300 mm PrismaSeT G floor-standing duct human-switchboard interface HSI 1 3 300 mm PrismaSeT G wall-mounted duct human-switchboard interface HSI 1 3 850 mm PrismaSeT G floor-standing enclosure human-switchboard interface HSI 4 3 650 mm 400 mm PrismaSeT P cubicle human-switchboard interface HSI 1 3 400 mm 400 mm PrismaSeT P cubicle human-switchboard interface HSI 1 3 300 mm 400 mm PrismaSeT P cubicle duct human-switchboard interface HSI 1 3

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.200 cm
Package 1 Width	9.500 cm
Package 1 Length	9.800 cm
Package 1 Weight	28.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	200
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	6.100 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes