



Main

Range	Linergy
Product or component type	Distribution block
Product name	Linergy DX
Range compatibility	Prisma PrismaSeT Pragma
Product compatibility	Spacial enclosures
IP degree of protection	IPxx B

Complementary

Location of connection	Top
Mounting support	DIN rail
Poles description	4P
[Ue] rated operational voltage	440 V AC
[Ui] rated insulation voltage	500 V AC
[Uimp] rated impulse withstand voltage	6 kV
[Ie] rated operational current	63 A at 40 °C
[In] rated current	63 A at 40 °C
Connections - terminals	Supply: tunnel type terminal16 mm ² (flexible) Supply: tunnel type terminal25 mm ² (rigid) Distribution: spring terminal (phase) , 12 x 2.5...6 mm ² (flexible) Distribution: spring terminal (phase) , 12 x 2.5...6 mm ² (rigid) Distribution: spring terminal (neutral) , 12 x 2.5...6 mm ² (flexible) Distribution: spring terminal (neutral) , 12 x 2.5...6 mm ² (rigid)
9 mm pitches	8
Total number of 18 mm modules	4
Height	96.5 mm
Width	72 mm
Depth	62 mm
Net weight	0.29 kg

Environment

Pollution degree	3
Resistance to incandescent wire	960 °C conforming to IEC 60695-2-11
Standards	IEC 60947-7-1 IEC 61439-2 IEC 61439-1
Product certifications	ASEFA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.5 cm
Package 1 Width	7.5 cm
Package 1 Length	10.5 cm
Package 1 Weight	328.0 g

Unit Type of Package 2	S03
Number of Units in Package 2	30
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	10.148 kg

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes