

Product data sheet

Characteristics

LVS04041

Distribution block, Linergy DX, 4P, 63A, 4 modules, 24 holes, quick connect bottom



Main

Range	Linergy
Product or component type	Distribution block
Product name	Linergy DX
Range compatibility	Prisma PrismaSeT Pragma
Product compatibility	Spacial enclosures
IP degree of protection	IPxx B

Complementary

Location of connection	Bottom
Mounting support	DIN rail
Poles description	4P
[Ue] rated operational voltage	440 V AC
[Ui] rated insulation voltage	500 V AC
[Uimp] rated impulse withstand voltage	6 kV
[Ie] rated operational current	63 A at 40 °C
[In] rated current	63 A at 40 °C
Connections - terminals	Supply: tunnel type terminal 16 mm ² (flexible) Supply: tunnel type terminal 25 mm ² (rigid) Distribution: spring terminal (phase), 12 x 2.5...6 mm ² (flexible) Distribution: spring terminal (phase), 12 x 2.5...6 mm ² (rigid) Distribution: spring terminal (neutral), 12 x 2.5...6 mm ² (flexible) Distribution: spring terminal (neutral), 12 x 2.5...6 mm ² (rigid)
9 mm pitches	8
Total number of 18 mm modules	4
Height	96.5 mm
Width	72 mm
Depth	62 mm
Net weight	0.29 kg

Environment

Pollution degree	3
Resistance to incandescent wire	960 °C conforming to IEC 60695-2-11
Standards	IEC 60947-7-1 IEC 61439-2 IEC 61439-1
Product certifications	ASEFA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.700 cm
Package 1 Width	7.800 cm
Package 1 Length	10.200 cm
Package 1 Weight	312.000 g

Unit Type of Package 2	S03
Number of Units in Package 2	30
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	9.883 kg

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes