



Main

Range	PrismaSeT
Range of product	PrismaSeT G
Product or component type	Connection
Product name	PrismaSeT PrismaSeT G duct
Accessory / separate part category	Current distribution accessory
Standards	IEC 61439-2, inside enclosure IEC 61439-1, inside enclosure
Product certifications	ASTA

Complementary

Cubicle-device connection	Linergy BS busbar
Installation description	Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm
Installed device	<p>ComPact: fixed NSX400 without earth leakage protection - control: toggle vertical installation</p> <p>ComPact: fixed NSX400 without earth leakage protection - control: direct front rotary handle vertical installation</p> <p>ComPact: fixed NSX400 with earth leakage protection - control: toggle vertical installation</p> <p>EasyPact: fixed CVS400 without earth leakage protection - control: toggle vertical installation</p> <p>EasyPact: fixed CVS630 without earth leakage protection - control: toggle vertical installation</p> <p>EasyPact: fixed CVS400 without earth leakage protection - control: direct front rotary handle vertical installation</p> <p>EasyPact: fixed CVS630 without earth leakage protection - control: direct front rotary handle vertical installation</p> <p>EasyPact: fixed CVS400 with earth leakage protection - control: toggle vertical installation</p> <p>EasyPact: fixed CVS630 with earth leakage protection - control: toggle vertical installation</p> <p>ComPact: fixed NSX630 without earth leakage protection - control: toggle vertical installation</p> <p>ComPact: fixed NSX630 without earth leakage protection - control: direct front rotary handle vertical installation</p> <p>ComPact: fixed NSX630 with earth leakage protection - control: toggle vertical installation</p> <p>ComPact: fixed INS320...400 - control: direct front rotary handle vertical installation</p> <p>ComPact: fixed INS500...630 - control: direct front rotary handle vertical installation</p> <p>ComPact: fixed INV320...400 - control: direct front rotary handle vertical installation</p> <p>ComPact: fixed INV500...630 - control: direct front rotary handle vertical installation</p>
[Ie] rated operational current	630 A
Net weight	2.28 kg

Quantity per set	Set of 1
------------------	----------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.5 cm
Package 1 Width	9.0 cm
Package 1 Length	29.0 cm
Package 1 Weight	2.238 kg
Unit Type of Package 2	P12
Number of Units in Package 2	36
Package 2 Height	21.0 cm
Package 2 Width	80.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	92.5 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations