



Main

Range	Linergy
Range of product	Linergy
Product or component type	Busbar
Product name	Linergy BW
Range compatibility	PrismaSeT PrismaSeT G enclosure PrismaSeT PrismaSeT P enclosure
IP degree of protection	IPxx B
Busbar description	Insulated bar
Quantity per set	Set of 1

Complementary

Poles description	4P
Installation direction	Vertical, operating position: rear
Installation description	Cubicle - width 650 mm Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm
[Ui] rated insulation voltage	750 V AC
[Uimp] rated impulse withstand voltage	8 kV
[Ie] rated operational current	400 A
[Icw] rated short-time withstand current	20 kA (1 s)
[Ipk] rated peak withstand current	52.5 kA
I ² t on activation	400000 kA ² .s
Permissible current	400 A
Length	1000 mm
Height	85 mm
Depth	45 mm
Net weight	6.36 kg
Type of busbar connection	M6 threaded hole
Connection pitch	Connection each 25 mm

Environment

Standards	IEC 61439-1 IEC 61439-2
Product certifications	ASTA
Mechanical robustness	Seismic tests structure reinforcement - 2.5G conforming to IEC 60068-2-57

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.500 cm
Package 1 Width	12.800 cm
Package 1 Length	113.000 cm
Package 1 Weight	6.648 kg
Unit Type of Package 2	P12

Number of Units in Package 2	48
Package 2 Height	50.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	320.000 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes