



Main

Range	Lineryg
Range of product	Lineryg
Product or component type	Connection
Product name	Lineryg BW
Product name	PrismaSeT PrismaSeT G enclosure PrismaSeT PrismaSeT P enclosure Lineryg Lineryg BW busbar
Provided equipment	With connection
Standards	IEC 61439-1, inside enclosure IEC 61439-2, inside enclosure
Product certifications	ASTA

Complementary

Cubicle-device connection	Lineryg BS busbar
Poles description	4P
Installation description	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Floor-standing enclosure - width 850 mm Pack enclosure - width 550 mm Cubicle - width 600 mm
Installed device	Multi9: NG125 ComPact: NG160 ComPact: INS160
[I _e] rated operational current	160 A
Material	Copper Plastic
Colour	Copper Black (RAL 9005)
Length	250 mm
Net weight	0.6 kg
Quantity per set	Set of 4

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.3 cm
Package 1 Width	5.3 cm
Package 1 Length	27.5 cm
Package 1 Weight	575.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	12
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	7.148 kg
Unit Type of Package 3	P12
Number of Units in Package 3	96

Package 3 Height	27.0 cm
Package 3 Width	80.0 cm
Package 3 Length	120.0 cm
Package 3 Weight	69.0 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations